

Safety Data Sheet
acc. to OSHA HCS

Printing date 08/22/2018

Reviewed on 08/22/2018

1 Identification

- **Product identifier**
- **Trade name:** V-AIR SOLID - ZERO
- **Article number:** V-SOLID ZERO
- **Application of the substance / the mixture** Air Freshener
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Vectair Systems Inc.
2095 Spicer Cove, Covington Way Distribution Center,
Memphis, TN 38134 United States
info@vectairsystems.com
- **Information department:** +1 901 373 7818 (during normal office hours)
- **Emergency telephone number:** INFOTRAC +1 800 535 5053 (International) +1-352-323-3500

2 Hazard(s) identification

- **Classification of the substance or mixture**



Skin Irrit. 2 H315 Causes skin irritation.

- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS07

- **Signal word** Warning
- **Hazard statements**
Causes skin irritation.
- **Precautionary statements**
Wash thoroughly after handling.
Wear protective gloves.
If on skin: Wash with plenty of water.
Specific treatment (see on this label).
If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/22/2018

Reviewed on 08/22/2018

Trade name: V-AIR SOLID - ZERO

(Contd. of page 1)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	1	Health = 1
FIRE	1	Fire = 1
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

112-27-6	Triethylene Glycol	≥2.5-<10%
57-55-6	Propylene glycol	≥2.5-<10%
88917-22-0	Dipropylene glycol monomethyl ether acetate	≥2.5-<10%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/22/2018

Reviewed on 08/22/2018

Trade name: V-AIR SOLID - ZERO

(Contd. of page 2)

· Protective Action Criteria for Chemicals

· PAC-1:

112-27-6	Triethylene Glycol	130 mg/m ³
102-76-1	(tri-)Acetin	19 mg/m ³
57-55-6	Propylene glycol	30 mg/m ³
9036-19-5	poly(oxyethylene) octylphenyl ether	13 mg/m ³
67-64-1	acetone	200 ppm

· PAC-2:

112-27-6	Triethylene Glycol	1,400 mg/m ³
102-76-1	(tri-)Acetin	210 mg/m ³
57-55-6	Propylene glycol	1,300 mg/m ³
9036-19-5	poly(oxyethylene) octylphenyl ether	140 mg/m ³
67-64-1	acetone	3200* ppm

· PAC-3:

112-27-6	Triethylene Glycol	4,400 mg/m ³
102-76-1	(tri-)Acetin	1,200 mg/m ³
57-55-6	Propylene glycol	7,900 mg/m ³
9036-19-5	poly(oxyethylene) octylphenyl ether	830 mg/m ³
67-64-1	acetone	5700* ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

57-55-6 Propylene glycol

WEEL	Long-term value: 10 mg/m ³
------	---------------------------------------

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the skin.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/22/2018

Reviewed on 08/22/2018

Trade name: V-AIR SOLID - ZERO

(Contd. of page 3)

- Avoid contact with the eyes and skin.
- **Breathing equipment:** Not required.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Goggles recommended during refilling.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

· Form:	Semi-Solid
· Color:	White Opaque
· Odor:	Characteristic
· Odor threshold:	Not determined.

· pH-value:	Not determined.
--------------------	-----------------

- **Change in condition**

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	>100 °C (>212 °F)

· Flash point:	>100 °C (>212 °F)
-----------------------	-------------------

· Flammability (solid, gaseous):	Not applicable.
---	-----------------

· Ignition temperature:	355 °C (671 °F)
--------------------------------	-----------------

· Decomposition temperature:	Not determined.
-------------------------------------	-----------------

· Auto igniting:	Product is not selfigniting.
-------------------------	------------------------------

· Danger of explosion:	Product does not present an explosion hazard.
-------------------------------	---

- **Explosion limits:**

· Lower:	Not determined.
· Upper:	Not determined.

· Vapor pressure at 20 °C (68 °F):	<2 hPa (<1.5 mm Hg)
---	---------------------

· Density at 20 °C (68 °F):	>1 g/cm ³ (>8.345 lbs/gal)
------------------------------------	---------------------------------------

· Relative density	Not determined.
---------------------------	-----------------

· Vapor density	Not determined.
------------------------	-----------------

· Evaporation rate	Not determined.
---------------------------	-----------------

(Contd. on page 5)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/22/2018

Reviewed on 08/22/2018

Trade name: V-AIR SOLID - ZERO

(Contd. of page 4)

- | | |
|---|--|
| · Solubility in / Miscibility with Water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 21.0 % |
| Water: | 17.0 % |
| VOC content: | 0.00 % |
| | Exempt Fragrance and no other VOCs |
| · Solids content: | 61.6 % |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

112-27-6 Triethylene Glycol

Oral	LD50	17,000 mg/kg (rat)
------	------	--------------------

57-55-6 Propylene glycol

Oral	LD50	30,000 mg/kg (rat)
Dermal	LD50	20,800 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

128-37-0	Butylated hydroxytoluene	3
----------	--------------------------	---

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/22/2018

Reviewed on 08/22/2018

Trade name: V-AIR SOLID - ZERO

(Contd. of page 5)

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Waste Disposal Recommendations:** Dispose in a safe manner in accordance with local/national regulations.
- **Additional Information:**
Empty container and removable plastic components should be recycled or placed in waste in accordance with local regulation.
- **Ecology – waste materials:** Avoid release to the environment, waste can be hazardous due to toxicity.

14 Transport information

- | | |
|--|-----------------|
| · UN-Number | |
| · DOT, IMDG, IATA | not regulated |
| · UN proper shipping name | |
| · DOT, IMDG, IATA | not regulated |
| · Transport hazard class(es) | |
| · DOT, IMDG, IATA | |
| · Class | not regulated |
| · Packing group | |
| · DOT, IMDG, IATA | not regulated |
| · Environmental hazards: | Not applicable. |
| · Special precautions for user | Not applicable. |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · UN "Model Regulation": | not regulated |

US

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/22/2018

Reviewed on 08/22/2018

Trade name: V-AIR SOLID - ZERO

(Contd. of page 6)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):
--

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):
--

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:
--

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:
--

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)
--

67-64-1 acetone	I
-----------------	---

· TLV (Threshold Limit Value established by ACGIH)

67-64-1 acetone	A4
-----------------	----

128-37-0 Butylated hydroxytoluene	A4
-----------------------------------	----

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).
--

· Hazard pictograms



GHS07

· Signal word Warning

· Hazard statements

Causes skin irritation.

· Precautionary statements

Wash thoroughly after handling.

Wear protective gloves.

If on skin: Wash with plenty of water.
--

Specific treatment (see on this label).

If skin irritation occurs: Get medical advice/attention.
--

Take off contaminated clothing and wash it before reuse.
--

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

US

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/22/2018

Reviewed on 08/22/2018

Trade name: V-AIR SOLID - ZERO

(Contd. of page 7)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Product safety department.

· **Date of preparation / last revision** 08/22/2018 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Irrit. 2: Skin corrosion/irritation – Category 2