

Three Phase String Inverter

SUN-15/17K-G05



2 MPP trackers, Max. efficiency up to 98.5%



Zero export application, VSG application



String intelligent monitoring (optional)



Wide output voltage range



Anti-PID function (Optional)

Deye

Stock Code: 605117.SH

Model	SUN-15K-G05	SUN-17K-G05
Input Side		
Max. DC Input Power (kW)	19.5	22.1
Max. DC Input Voltage (V)		1000
Start-up DC Input Voltage (V)		250
MPPT Operating Range (V)		200-850
Max. DC Input Current (A)		13+26
Max. Short Circuit Current (A)		19.5+39
No.of MPP Trackers		2
No.of Strings per MPP Tracker		1+2
Output Side		
Rated Output Power (kW)	15	17
Max. Active Power (kW)	16.5	18.7
Rated Output Voltage/Range (V)	3L/N/PE 220/380V, 230/400V 0.85Un-1.1Un (this may vary with grid standards)	
Rated Grid Frequency (Hz)	50 / 60 (Optional)	
Operating Phase	Three Phase	
Rated AC Grid Output Current (A)	22.7/21.7	25.8/24.6
Max. AC Output Current (A)	25/23.9	28.3/27.1
Output Power Factor	0.8 leading to 0.8 lagging	
Total Harmonics Current Distortion (THDi)	<3%	
DC Injection Current (mA)	<0.5%	
Grid Frequency Range	45~55 or 55~65 (Optional)	
Efficiency		
Max. Efficiency	98.5%	
Euro Efficiency	97.5%	
MPPT Efficiency	>99%	
Protection		
DC Reverse-Polarity Protection	Yes	
AC Short Circuit Protection	Yes	
AC Output Overcurrent Protection	Yes	
Output Overvoltage Protection	Yes	
Insulation Resistance Protection	Yes	
Ground Fault Monitoring	Yes	
Anti-islanding Protection	Yes	
Temperature Protection	Yes	
Integrated DC Switch	Yes	
Remote Software Upload	Yes	
Remote Change of Operating Parameters	Yes	
Surge Protection	DC Type II / AC Type II	
General Data		
Cabinet Size (WxHxD mm)	333×472×203 (Excluding Connectors and Brackets)	
Weight (kg)	15	
Topology	Transformerless	
Internal Consumption	<1W (Night)	
Running Temperature	-25-65°C, >45°C Derating	
Ingress Protection	IP65	
Noise Emission (Typical)	≤40 dB	
Cooling Concept	Smart Cooling	
Permissible Altitude (m)	4000	
Warranty	5 Years	
Grid Connection Standard	IEC 61727, IEC 62116, CEI 0-21, EN 50549, NRS 097, RD 140, UNE 217002, G98, G99, VDE 4105	
Operating Surroundings Humidity	0-100%	
Safety EMC / Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2	
Features		
Display	LCD1602	
Interface	RS485/RS232/Wifi/LAN	