

Instant Hot Water Tanks



Choose the right model for you

NEOTANK



Summary The InSinkErator® NeoTank heats water up to 99°C, has a touch screen display and dry start protection. This is our most energy efficient model to date and is 40% more energy efficient than the Standard Edition tank.

STANDARD EDITION





The InSinkErator® Standard Edition Tank heats water up to 98°C. You have the ability to adjust the temperature using the mechanical, snap-action thermostat. This model is marginally more compact than the NeoTank.

Specifications

Dimensions (mm)	286 H x 157 W x 206 D	258 H x 157 W x 172 D
Warranty	2 year, In-Home replacement	1 yr; In-Home Replacement
Temperature Range	88-99°C	71-98°C
Tank Capacity	2.5 litres	2.5 litres
Thermostat	Touch Screen Electronic	Mechanical, Snap-action
Wattage	1300 Watt	750 Watt
Tank Temperature Variance (Total)	1°C total range; +/-0.5°C	8°C total range (+0°C, -8°C)
Tank Type	Unpressurised	Unpressurised
Indicators, Alarms, Smart Features	On/Off Power, 1°C temp bars, flashing dry start	None
Thermostat Accuracy	1°C	1°C

The fittings and connections on top of both tanks are the same. Therefore, you have an easy changeover, whichever InSinkErator tap you have.

Dimensions (mm)



InSinkErator EMEA
Suite 10, Building 6
Hatters Lane
Croxley Green Business Park
Watford, Herts WD18 8YH
United Kingdom

01923 297 880
www.insinkerator.co.uk

