for up to 99 days

reduces runoff

· Added knockouts for

· Rain sensor bypass

additional flexibility

• Warranty period: 2 years

• Solar Sync® Delay feature allows adjustments to be postponed

· Cycle and Soak feature built in:

• One-touch manual start and advance

# PRO-C® & PCC

Number of Stations: 4 - 16, 6 & 12

Type: Modular & Fixed

#### **FEATURES**

- Number of stations:
  - Pro-C: 4 16
  - PCC: 6 & 12
- · Type:
  - Pro-C: Modular
  - PCC: Fixed
- Enclosures: Indoor or outdoor plastic Non-volatile memory
- Independent irrigation programs: 3
- Independent lighting programs: 3
- · Start times per program: 4
- · Max. station run time: 6 hours
- ▶ Built in Solar Sync
- ► Easy Retrieve<sup>™</sup> memory
- ▶ QuickCheck™
- ► Automatic short circuit protection
- ► Seasonal Adjustment: Global or automatic updates with Solar Sync
- ► Delay between stations
- Sensor programmability
- ► Non-Water Days

#### **Plastic Indoor**

Height: 8.25' Width: 9.5" Depth: 3.75"



### **Plastic Outdoor**

Height: 9" Width: 10" Depth: 4.5"



#### PCM-300 and PCM-900 Expansion Modules

These modules are compatible with the new Pro-C 400 series.

## **ELECTRICAL SPECIFICATIONS**

- Transformer input: 120 VAC or 230 VAC (international model)
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.28 A
- · Sensor inputs: 1

# **APPROVALS**

- CE, UL, cUL, C-tick, FCC
- Advanced Feature descriptions on page 89

PRO-C SPECIFICATION BUILDER: ORDER1 + 2 + 3 + 4				PC-SERIES STATION EXPANSION	
1 Models	2 Transformer	3 Indoor/Outdoor	4 Options	Modules	Description
PC-4 = 4-station base module controller PCC-6 = 6-Station PCC-12 = 12-Station	<b>00</b> = 120 VAC <b>01</b> = 230 VAC	(blank) = Outdoor Model (internal transformer) i = Indoor Model (plug-in transformer)	(blank) = No option  E = 230 VAC with European Connections  A = 230 VAC with Australian Connections (outdoor models have internal transformer	PCM-300	3-station plug-in module: Use to increase station count from 4 to 7, 7 to 10, and 10 to 13 9-station plug-in module: Use to increase station count
			with cord)		from 7 to 16

#### **Examples:**

PC-400 = Modular 4-station outdoor base unit, internal 120 VAC transformer, and plastic cabinet PCC-601i - E = Fixed 6-station indoor controller, plug-in 230 VAC transformer with European

connections, and plastic cabinet

PCC-1200 = Fixed 12-station outdoor controller, Internal 120 VAC transformer, and plastic cabinet