

OCTANE

CERAMIC COATING FOR

— PAINT —
— WHEELS —
— TRIM —



“THE PROCESS”

THIS PROCESS ASSUMES



1

WASH

WASH VEHICLE THOROUGHLY WITH WABAM WHITEOUT.

2

CLAY

IF CONTAMINATED, USE A CLAY BAR TO CLEAN THE PAINT AND WHEELS.

3

COMPOUND POLISH

IF PAINT CORRECTION IS REQUIRED, DO SO BEFORE APPLICATION.



4

PREP

SPRAY WABAM STAGE ON SURFACE TO REMOVE ANY CONTAMINATION, WIPE WITH MICROFIBER TOWEL.

5

APPLY OCTANE

SATURATE APPLICATOR PAD WITH WABAM OCTANE AND APPLY ONTO SURFACE.

6

ALLOW FLASH

WAIT 8 MINS FOR OCTANE TO FLASH AND LEVEL/BUFF OFF WITH MICROFIBER TOWEL.

7

CURE TIME

WAIT 2 HOURS BEFORE GETTING COATING WET.

“THE PRODUCT”

WABAM OCTANE PROVIDES A SUPER-SLICK AND GLOSSY PAINT PROTECTION WITH REVOLUTIONARY NEW FEATURES WHICH IN DURABILITY, HARDNESS, CHEMICAL RESISTANCE AND THE UNBELIEVABLE FAST AND EASY INSTALL PROCESS!

TECHNICAL DATA

EFFECTIVENESS

8+ YEARS (PENDING ENVIRONMENTAL FACTORS & MAINTENANCE)

HARDNESS

10H

APPLICATION

WIPE ON / BUFF OFF

BOTTLE SIZE

60 ML

SHELF LIFE (UNOPENED)

1 YEAR

SHELF LIFE (OPENED)

90 DAYS

FINISH

HIGH GLOSS

USES



8 MIN. FLASH TIME!*

2 HOUR CURE TIME!



COMPLETE UV PROTECTION

SUPER SLICK FINISH

EXTREME HYDROPHOBIC FEATURES

OUTSTANDING CHEMICAL RESISTANCE

*8 MINUTE FLASH TIME IN NORMAL NON-HUMID CONDITIONS

**1 PRODUCT FOR ALL....
PAINT, PLASTIC, TRIM AND WHEELS!**

REPORTED WITH



GETWABAM.COM