



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## WABAM Octane

Version number: GHS 2.0  
Replaces version of: 2022-03-24 (GHS 1)

Revision: 2022-03-24

### SECTION 1: Identification

#### 1.1 Product identifier

Trade name **WABAM Octane**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Vehicle coating  
HS code 3208.90.00.

#### 1.3 Details of the supplier of the safety data sheet

WABAM a brand of Supply Zone, LLC  
620 Wacker Drive  
Hartford WI 53029  
262-573-3016

sales@getwabam.com  
www.getwabam.com

#### 1.4 Emergency telephone number

Emergency information service USA 1.800.535.5053, INTL 1.352.323.3500  
24 hr emergency information

### SECTION 2: Hazard(s) identification

#### 2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.10	acute toxicity (oral)	4	Acute Tox. 4	H302
A.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
A.3	serious eye damage/eye irritation	1	Eye Dam. 1	H318
A.7	reproductive toxicity	2	Repr. 2	H361f
A.10	aspiration hazard	1	Asp. Tox. 1	H304
B.6	flammable liquid	3	Flam. Liq. 3	H226

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources. The mixture contains a substance that was identified as a PBT (persistent, bioaccumulative and toxic). The mixture contains a substance that was identified as vPvB (very persistent and very bioaccumulative).

Additional information

Containing a PBT-/vPvB-substance in a concentration of  $\geq 0,1\%$ .

#### 2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS02, GHS05,  
GHS07, GHS08





# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## WABAM Octane

Version number: GHS 2.0  
Replaces version of: 2022-03-24 (GHS 1)

Revision: 2022-03-24

### - Hazard statements

H226	Flammable liquid and vapor.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H361f	Suspected of damaging fertility.

### - Precautionary statements

P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P302+P352	If on skin: Wash with plenty of water.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321	Specific treatment (see on this label).
P330	Rinse mouth.
P331	Do NOT induce vomiting.
P362	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

### - Hazardous ingredients for labelling

octamethylcyclotetrasiloxane, Alkyl Polysilicates, Cyclosilazanes, di-Me, Me Hydrogen, polymers with di-Me, Me hydrogen silazanes, and 2,4-TDI, distillates (petroleum) hydrotreated, light

## 2.3 Other hazards

Hazards not otherwise classified

Very toxic to aquatic life with long lasting effects (GHS category 1: aquatic toxicity - acute and/or chronic).

Results of PBT and vPvB assessment

Containing a PBT-/vPvB-substance in a concentration of  $\geq 0,1\%$ .

Endocrine disrupting properties

Contains an endocrine disruptor (EDC) in a concentration of  $\geq 0,1\%$ .

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not relevant (mixture)

### 3.2 Mixtures



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## WABAM Octane

Version number: GHS 2.0  
Replaces version of: 2022-03-24 (GHS 1)

Revision: 2022-03-24

### Description of the mixture

Hazardous ingredients acc. to GHS				
Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
octamethylcyclotetrasiloxane	CAS No 556-67-2	≥ 1	Repr. 2 / H361f Flam. Liq. 3 / H226	PBT vPvB
distillates (petroleum) hydro- treated, light	CAS No 64742-47-8	≥ 10	Asp. Tox. 1 / H304	
Alkyl Polysilicates	CAS No Trade Secret	15 - < 80	Acute Tox. 4 / H302 Skin Corr. 1B / H314	
Cyclosilazanes, di-Me, Me Hydrogen, polymers with di- Me, Me hydrogen silazanes, and 2,4-TDI	CAS No trade secret	20 - < 70	Acute Tox. 4 / H302 Skin Irrit. 2 / H315 Flam. Liq. 2 / H225	
decamethylcyclopentasilox- ane	CAS No 541-02-6	5 - < 10	Flam. Liq. 4 / H227	PBT vPvB
methanol	CAS No 67-56-1	0.17 - < 0.39	Acute Tox. 3 / H301 Acute Tox. 3 / H311 Acute Tox. 3 / H331 STOT SE 1 / H370 Flam. Liq. 2 / H225	

#### Notes

PBT: The substance was identified as a PBT (persistent, bioaccumulative and toxic)  
vPvB: The substance was identified as a vPvB (very persistent and very bioaccumulative)

For full text of abbreviations: see SECTION 16. Exact percentage of ingredients is withheld as a trade secret.  
*This table, if present, includes all GHS classified ingredients present above their cut-off limits, even if the finished product is not classified as hazardous by GHS.*

## SECTION 4: First-aid measures

### 4.1 Description of first-aid measures

#### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

#### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

#### Following skin contact

Wash with plenty of soap and water.

#### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing.

#### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## WABAM Octane

Version number: GHS 2.0  
Replaces version of: 2022-03-24 (GHS 1)

Revision: 2022-03-24

### SECTION 5: Fire-fighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO<sub>2</sub>)

#### 5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NO<sub>x</sub>), Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

#### 6.2 Environmental precautions

If substance has entered a water course or sewer, inform the responsible authority.

#### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

#### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## WABAM Octane

Version number: GHS 2.0  
Replaces version of: 2022-03-24 (GHS 1)

Revision: 2022-03-24

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

##### Recommendations

##### - Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

##### - Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

##### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

#### 7.2 Conditions for safe storage, including any incompatibilities

##### Managing of associated risks

##### - Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

##### - Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

##### - Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

##### - Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

#### 7.3 Specific end use(s)

See section 16 for a general overview.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
US	methanol	67-56-1	TLV®	200		250				H	ACGIH® 2019
US	methyl alcohol	67-56-1	REL	200 (10 h)	260 (10 h)	250	325				NIOSH REL
US	methyl alcohol	67-56-1	PEL	200	260						29 CFR 1910.1000



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## WABAM Octane

Version number: GHS 2.0  
Replaces version of: 2022-03-24 (GHS 1)

Revision: 2022-03-24

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
US	methyl alcohol (methanol)	67-56-1	PEL (CA)	200	260	250	325	1,000			Cal/ OSHA PEL
US	graphite	7782-42-5	PEL (CA)		2.5					natural, r	Cal/ OSHA PEL
US	graphite	7782-42-5	REL		2.5 (10 h)					natural, r	NIOSH REL
US	graphite	7782-42-5	PEL	530						partml, r, natural	29 CFR 1910.1000
US	graphite	7782-42-5	TLV®		2					r, exGraphFib	ACGIH® 2019
US	graphite	7782-42-5	REL							synthetic, appx-D	NIOSH REL
US	graphite	7782-42-5	PEL (CA)		10					synthetic, dust	Cal/ OSHA PEL
US	graphite	7782-42-5	PEL		15					synthetic, i, dust	29 CFR 1910.1000
US	graphite	7782-42-5	PEL (CA)		5					synthetic, r	Cal/ OSHA PEL
US	graphite	7782-42-5	PEL		5					synthetic, r, dust	29 CFR 1910.1000

### Notation

appx-D	see Appendix D - Substances with No Established RELs
Ceiling-C	ceiling value is a limit value above which exposure should not occur
dust	as dust
exGraphFib	except graphite fibers
H	absorbed through the skin
i	inhalable fraction
natural	natural
partml	particles/ml
r	respirable fraction
STEL	short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
synthetic	synthetic
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## WABAM Octane

Version number: GHS 2.0  
Replaces version of: 2022-03-24 (GHS 1)

Revision: 2022-03-24

Biological limit values						
Country	Name of agent	Parameter	Notation	Identifier	Value	Source
US	methanol	methanol		BEI®	15 mg/l	ACGIH® 2019

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Alkyl Polysilicates	Trade Secret	DNEL	14 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
Alkyl Polysilicates	Trade Secret	DNEL	2 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects
octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
decamethylcyclopentasiloxane	541-02-6	DNEL	97 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects
decamethylcyclopentasiloxane	541-02-6	DNEL	24 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
decamethylcyclopentasiloxane	541-02-6	DNEL	97 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
decamethylcyclopentasiloxane	541-02-6	DNEL	24 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
methanol	67-56-1	DNEL	130 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
methanol	67-56-1	DNEL	130 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects
methanol	67-56-1	DNEL	130 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
methanol	67-56-1	DNEL	130 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
methanol	67-56-1	DNEL	20 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
methanol	67-56-1	DNEL	20 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## WABAM Octane

Version number: GHS 2.0  
Replaces version of: 2022-03-24 (GHS 1)

Revision: 2022-03-24

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
octamethylcyclotetrasiloxane	556-67-2	PNEC	10 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.059 mg/kg	pelagic organisms	sediment	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	1.7 mg/kg	(top) predators	water	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.44 µg/l	aquatic organisms	freshwater	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.044 µg/l	aquatic organisms	marine water	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	3 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.3 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.59 mg/kg	benthic organisms	sediment	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.16 mg/kg	terrestrial organisms	soil	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	10 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	11 mg/kg	benthic organisms	sediment	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	13 mg/kg	(top) predators	water	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	1.1 mg/kg	pelagic organisms	sediment	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	1.2 µg/l	aquatic organisms	freshwater	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	0.12 µg/l	aquatic organisms	marine water	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	11 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	1.1 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	2.5 mg/kg	terrestrial organisms	soil	short-term (single instance)
methanol	67-56-1	PNEC	100 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
methanol	67-56-1	PNEC	77 mg/kg	benthic organisms	sediment	short-term (single instance)



## WABAM Octane

Version number: GHS 2.0  
Replaces version of: 2022-03-24 (GHS 1)

Revision: 2022-03-24

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
methanol	67-56-1	PNEC	7.7 mg/kg	pelagic organisms	sediment	short-term (single instance)
methanol	67-56-1	PNEC	1,540 mg/l	aquatic organisms	water	intermittent release
methanol	67-56-1	PNEC	21 mg/l	aquatic organisms	freshwater	short-term (single instance)
methanol	67-56-1	PNEC	2.1 mg/l	aquatic organisms	marine water	short-term (single instance)
methanol	67-56-1	PNEC	100 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
methanol	67-56-1	PNEC	77 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
methanol	67-56-1	PNEC	7.7 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
methanol	67-56-1	PNEC	100 mg/kg	terrestrial organisms	soil	short-term (single instance)

### 8.2 Exposure controls

#### Appropriate engineering controls

General ventilation.

#### Individual protection measures (personal protective equipment)

##### Eye/face protection

Wear eye/face protection.

##### Skin protection

###### - Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

###### - Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

#### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## WABAM Octane

Version number: GHS 2.0  
Replaces version of: 2022-03-24 (GHS 1)

Revision: 2022-03-24

Physical state	liquid
Color	grey
Particle	not relevant (liquid)
Odor	characteristic

### Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	>65 °C at 1 atm
Flash point	55 °C at 101 kPa
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)

### Explosive limits

- Lower explosion limit (LEL)	0.6 vol%
- Upper explosion limit (UEL)	4.9 vol%

Vapor pressure	132 Pa at 25 °C
Density	0.95 g/ml
Vapor density	this information is not available
Solubility(ies)	not determined

### Partition coefficient

- n-octanol/water (log KOW)	this information is not available
-----------------------------	-----------------------------------

Auto-ignition temperature	262 °C (auto-ignition temperature (liquids and gases))
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

## 9.2 Other information

Temperature class (USA, acc. to NEC 500)	T2B (maximum permissible surface temperature on the equipment: 260 °C)
--	--



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## WABAM Octane

Version number: GHS 2.0  
Replaces version of: 2022-03-24 (GHS 1)

Revision: 2022-03-24

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

#### 10.2 Chemical stability

See below "Conditions to avoid".

#### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

#### 10.5 Incompatible materials

Oxidizers

#### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Harmful if swallowed.

- Acute toxicity estimate (ATE)

Oral 914 mg/kg

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
Cyclosilazanes, di-Me, Me Hydrogen, polymers with di-Me, Me hydrogen silazanes, and 2,4-TDI	trade secret	oral	500 mg/kg
Alkyl Polysilicates	Trade Secret	oral	500 mg/kg
methanol	67-56-1	oral	100 mg/kg
methanol	67-56-1	inhalation: gas	700 ppmV/4h
methanol	67-56-1	inhalation: dust/mist	0.5 mg/l/4h



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## WABAM Octane

Version number: GHS 2.0  
Replaces version of: 2022-03-24 (GHS 1)

Revision: 2022-03-24

### Skin corrosion/irritation

Causes skin irritation.

### Serious eye damage/eye irritation

Causes serious eye damage.

### Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

### Carcinogenicity

Shall not be classified as carcinogenic.

### Reproductive toxicity

Suspected of damaging fertility.

### Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

### Aspiration hazard

May be fatal if swallowed and enters airways.

## SECTION 12: Ecological information

### 12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Alkyl Polysilicates	Trade Secret	LC50	>934 mg/l	fish	96 h
Alkyl Polysilicates	Trade Secret	EC50	331 mg/l	aquatic invertebrates	48 h
octamethylcyclotetrasiloxane	556-67-2	LC50	>22 µg/l	fish	96 h
octamethylcyclotetrasiloxane	556-67-2	EC50	>1,000 mg/l	aquatic invertebrates	96 h
decamethylcyclopentasiloxane	541-02-6	LC50	>16 µg/l	fish	96 h
decamethylcyclopentasiloxane	541-02-6	EC50	>2.9 µg/l	aquatic invertebrates	48 h
methanol	67-56-1	LC50	15,400 mg/l	fish	96 h
methanol	67-56-1	EC50	12,700 mg/l	fish	96 h
methanol	67-56-1	ErC50	22,000 mg/l	algae	96 h



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## WABAM Octane

Version number: GHS 2.0  
Replaces version of: 2022-03-24 (GHS 1)

Revision: 2022-03-24

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Alkyl Polysilicates	Trade Secret	EC50	43 mg/l	microorganisms	5.75 h
octamethylcyclotetrasiloxane	556-67-2	LC50	10 µg/l	fish	14 d
octamethylcyclotetrasiloxane	556-67-2	EC50	>500 mg/l	aquatic invertebrates	24 h
decamethylcyclopentasiloxane	541-02-6	LC50	>16 µg/l	fish	14 d
decamethylcyclopentasiloxane	541-02-6	EC50	>15 µg/l	aquatic invertebrates	21 d

### 12.2 Persistence and degradability

Data are not available.

### 12.3 Bioaccumulative potential

The substance fulfills the very bioaccumulative criterion.

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

The mixture contains a substance that was identified as a PBT (persistent, bioaccumulative and toxic). The mixture contains a substance that was identified as vPvB (very persistent and very bioaccumulative).

### 12.6 Endocrine disrupting properties

Contains an endocrine disruptor (EDC) in a concentration of  $\geq 0,1\%$ .

### 12.7 Other adverse effects

Data are not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## WABAM Octane

Version number: GHS 2.0  
Replaces version of: 2022-03-24 (GHS 1)

Revision: 2022-03-24

### SECTION 14: Transport information

#### 14.1 UN number

DOT	UN 1993
IMDG-Code	UN 1993
ICAO-TI	UN 1993

#### 14.2 UN proper shipping name

DOT	Flammable liquid, n.o.s.
IMDG-Code	FLAMMABLE LIQUID, N.O.S.
ICAO-TI	Flammable liquid, n.o.s.
Technical name (hazardous ingredients)	Cyclosilazanes, di-Me, Me Hydrogen, polymers with di-Me, Me hydrogen silazanes, and 2,4-TDI, octamethylcyclotetrasiloxane

#### 14.3 Transport hazard class(es)

DOT	3
IMDG-Code	3
ICAO-TI	3

#### 14.4 Packing group

DOT	III
IMDG-Code	III
ICAO-TI	III

#### 14.5 Environmental hazards

	hazardous to the aquatic environment
Environmentally hazardous substance (aquatic environment)	decamethylcyclopentasiloxane

#### 14.6 Special precautions for user



There is no additional information.

#### 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

#### Information for each of the UN Model Regulations

##### Transport of dangerous goods by road or rail (49 CFR US DOT)

Particulars in the shipper's declaration	UN1993, Flammable liquid, n.o.s., (contains: Cyclosilazanes, di-Me, Me Hydrogen, polymers with di-Me, Me hydrogen silazanes, and 2,4-TDI, octamethylcyclotetrasiloxane), 3, III, environmentally hazardous
Reportable quantity (RQ)	2,873,563 lbs (1,304,598 kg) (methanol)
Danger label(s)	3, fish and tree
 	
Environmental hazards	yes (hazardous to the aquatic environment)
Special provisions (SP)	B1, B52, IB3, T4, TP1, TP29
ERG No	128



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## WABAM Octane

Version number: GHS 2.0  
Replaces version of: 2022-03-24 (GHS 1)

Revision: 2022-03-24

### International Maritime Dangerous Goods Code (IMDG)

Marine pollutant YES (hazardous to the aquatic environment) (decamethylcyclopentasiloxane)  
Danger label(s) 3, fish and tree



Special provisions (SP) 223, 274, 955  
Excepted quantities (EQ) E1  
Limited quantities (LQ) 5 L  
EmS F-E, S-E  
Stowage category A

### International Civil Aviation Organization (ICAO-IATA/DGR)

Environmental hazards YES (hazardous to the aquatic environment)  
Danger label(s) 3



Special provisions (SP) A3  
Excepted quantities (EQ) E1  
Limited quantities (LQ) 10 L

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations specific for the product in question

#### National regulations (United States)

**Toxic Substance Control Act (TSCA)** all ingredients are listed

#### Superfund Amendment and Reauthorization Act (SARA TITLE III )

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings			
Name of substance	CAS No	Remarks	Effective date
methanol	67-56-1		1986-12-31

#### Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
methanol	67-56-1		3 4	5000 (2270)

#### Legend

- 3 "3" indicates that the source is section 112 of the Clean Air Act
- 4 "4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## WABAM Octane

Version number: GHS 2.0  
Replaces version of: 2022-03-24 (GHS 1)

Revision: 2022-03-24

### Clean Air Act

none of the ingredients are listed

### Right to Know Hazardous Substance List

#### - Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
Cyclosilazanes, di-Me, Me Hydrogen, polymers with di-Me, Me hydrogen silazanes, and 2,4-TDI	trade secret	refractory resin	
Alkyl Polysilicates	Trade Secret	resin	
octamethylcyclotetrasiloxane	556-67-2	solvents	Canada PBiTs CECBP - Priority Chemicals EC PBTs
distillates (petroleum) hydrotreated, light	64742-47-8	solvents	
Graphene	7782-42-5	surface modifier	
fluorine modified silicone fluid	115361-68-7	surface modifier	
decamethylcyclopentasiloxane	541-02-6	solvents	Canada PBiTs CECBP - Priority Chemicals EC PBTs
polydimethylsiloxane	63148-62-9	surface modifier	
polytrimethylhydrosilylsiloxane	68988-56-7	surface modifier	
trimethylsiloxysilicate	68988-56-7	resin	
methanol	67-56-1	alcohols	CA TACs NTP OHAT - Repr. or Dev. Toxicants OEHHA RELs Prop 65
tetra(trimethylsiloxy)silane	3555-47-3	surface modifier	Canada PBiTs

#### - Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
methanol	67-56-1				1.0 %

#### - Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
methanol	67-56-1		TE F3

#### Legend

F3 Flammable - Third Degree  
TE Teratogenic





# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## WABAM Octane

Version number: GHS 2.0  
Replaces version of: 2022-03-24 (GHS 1)

Revision: 2022-03-24

### - Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
METHANOL	67-56-1	E

#### Legend

E Environmental hazard

### - Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
methanol	67-56-1	T, F

#### Legend

F Flammability (NFPA®)  
T Toxicity (ACGIH®)

### California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals				
Name acc. to inventory	CAS No	Conc.	Remarks	Type of the toxicity
methanol	67-56-1	0.17 wt%		developmental

### VOC content

- Regulated Volatile Organic Compounds (VOC-EPA) 0.17 %
- Regulated Volatile Organic Compounds (VOC-Cal ARB) 0.17 %

### Industry or sector specific available guidance(s)

#### NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	3	major injury likely unless prompt action is taken and medical treatment is given
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

Chronic: chronic hazard  
Flammability: flammability hazards  
Health: health hazard  
Personal protection: personal protective equipment (PPE) for normal use  
Physical hazard: reactivity

#### NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## WABAM Octane

Version number: GHS 2.0  
Replaces version of: 2022-03-24 (GHS 1)

Revision: 2022-03-24

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Health	3	material that, under emergency conditions, can cause serious or permanent injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

### National inventories

Country	Inventory	Status
CA	DSL	not all ingredients are listed
CA	NDSL	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed

#### Legend

DSL Domestic Substances List (DSL)  
NDSL Non-domestic Substances List (NDSL)  
REACH Reg. REACH registered substances  
TSCA Toxic Substance Control Act

## 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information, including date of preparation or last revision

### Indication of changes (revised safety data sheet)

Alignment to regulation: Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book").  
Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
1.3	Details of the supplier of the safety data sheet: WABAM a brand of Supply Zone 620 Wacker Drive Hartford WI 53029 262-573-3016  sales@getwabam.com www.getwabam.com	Details of the supplier of the safety data sheet: WABAM a brand of Supply Zone, LLC 620 Wacker Drive Hartford WI 53029 262-573-3016  sales@getwabam.com www.getwabam.com	yes

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2019	From ACGIH®, 2019 TLVs® and BEIs® Book. Copyright 2019. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: <a href="http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement">http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement</a>



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## WABAM Octane

Version number: GHS 2.0  
Replaces version of: 2022-03-24 (GHS 1)

Revision: 2022-03-24

Abbr.	Descriptions of used abbreviations
Acute Tox.	Acute toxicity
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Cal ARB	California Air Resources Board
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EmS	Emergency Schedule
EPA	Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
ERG No	Emergency Response Guidebook - Number
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance
HS	Harmonized Commodity Description and Coding System (Harmonized System, drawn up by the World Customs Organisation)
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LHS	Lower hazard substance
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NFPA®	National Fire Protection Association (United States)
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## WABAM Octane

Version number: GHS 2.0  
Replaces version of: 2022-03-24 (GHS 1)

Revision: 2022-03-24

Abbr.	Descriptions of used abbreviations
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Repr.	Reproductive toxicity
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TLV®	Threshold Limit Values
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

### Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H227	Combustible liquid.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H361f	Suspected of damaging fertility.
H370	Causes damage to organs.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## WABAM Octane

Version number: GHS 2.0  
Replaces version of: 2022-03-24 (GHS 1)

Revision: 2022-03-24

---

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.