

STYLE NAME	OzoGrip® Fast Track III
SIZE	7.08" x 47.24" planks. 10 planks / carton 2.325 s/f per tile. 23.25 s/f carton
GAUGE	5.0 mm
WEAR LAYER	.5mm (20mil)
FINISH	Ozocoat technology (added for anti microbial, anti-fungal and anti-bacterial protection) SCS-EC10.3-2014
FLOORSCORE	Certified SCS-FS-03764
INDOOR QUALITY	SCS-EC10.3-2014
COEFICIENT OF FRICTION	ASTM D2047 (Jame Method)
REFERENCED SPECIFICATIONS	ASTM F-1700, Class III, Type B, Embossed Surface (Meets or exceeds requirements for composition, size, thickness, squareness, flexibility, dimensional stability, and resistance to chemicals)
CRITICAL RADIANT FLUX	ASTM E648-08 class I-1.06 watts cm2
FLEXIBILITY	ASTM F-137-08 Passes 6MM Mandrel
STATIC LOAD LIMIT	ASTM F970-07 Passes 1,000 PSI Modified
MAINTENANCE	Requires no wax, no stripping, no buffing or toxic seal coat.
WARRANTY	10-year limited commercial warranty
RESISTANCE TO CHEMICALS	ASTM F925-02. No surface dulling, surface attack, color change (5 acetic acid, 70% isoproply alcohol, mineral oil, 5% sodium hydroxide, 5% hydrochloric acid, 5% ammonia, bleach, 5% phenol, gasolina, sulfuric acid, kerosene, and olive oil)
MOISTURE MAXIMUMS	Up to 8lbs - Calcium Chloride or Hydrostatic Pressure - PH no greater than 11 -11 RH no greater than 85%
IMPACT SOUND TRANSMISSION	ASTM E989-06. IIC57