

STYLE NAME	OzoGrip® Fantasy
GAUGE / WEAR LAYER	5.0 mm / 20mil
SIZE	7.08" X 47.24" planks. 10 planks / carton. 23,25 s/f carton
WARRANTY	15-year limited commercial warranty / Lifetime residential
FINISH	OzoCoat+™ Technology (added for anti-microbial, anti-fungal and anti-bacterial protection)
MAINTENANCE	Requires no wax, no stripping, no buffing or toxic seal coat
INDOOR AIR QUALITY	FloorScore® Indoor Air Quality Certified to SCS-EC10.3-2014 v4.1 Registration # SCS-FS-04606
STATIC COEFFICIENT OF FRICTION	ASTM D2047 (James Method)
CRITICAL RADIANT FLUX	ASTM E648-08 class 1-1.06 watts cm2
FLEXIBILITY / STATIC LOAD LIMIT	ASTM F-137-08 Passes 6MM Mandrel/ ASTM F970-07 Passes 1,000 PSI Modified
RESISTANCE TO CHEMICALS	ASTM F925-02. No surface dulling, surface attack, color change (5 acetic acid, 70% isopropyl alcohol, mineral oil, 5% sodium hydroxide, 5% hydrochloric acid, 5% ammonia, bleach, 5% phenol, gasoline, sulfuric acid, kerosene, and olive oil)
IMPACT SOUND TRANSMISSION	ASTM E989-06. IIC57
REFERENCED SPECIFICATIONS	ASTM F-1700, Class 111, Type B, Embossed Surface (Meets or exceeds requirements for composition, size, thickness, squareness, flexibility, dimensional stability, and resistance to chemicals)