

STYLE NAME	OzoGrip® WOVEN
COMPOSITION	Virgin Vinyl – Phthalate Free
INSTALLATION	Glue Down; Perimeter Glue
SIZE	19.68” x 39.37”
GAUGE	5.0mm
WEAR LAYER	20 mil
EDGE	Square
FINISH	Ozocoat+ Technology Advanced Ceramic Bead Barrier + Coating, Antifungal, Antibacterial, No Wax, No Buff
CERTIFICATIONS	FloorScore®; Environmental Product Declaration (EPD); ISO-9001 / ISO-14001
WARRANTY	Lifetime Residential / 10-Year Commercial
REFERENCE SPECIFICATIONS	ASTM F-1700 Solid Vinyl Floor Tile – Class III, Type B-Embossed Meets & Exceeds Passing Requirements for composition, size, thickness, squareness, flexibility, dimensional stability and resistance to chemicals.
RADIANT PANEL	ASTM E-648 Critical Radiant Flux – Class I Meets & Exceeds Passing Requirements
STATIC LOAD LIMIT	ASTM-F-970 Meets & Exceeds Passing Requirements
SLIP RESISTANCE	ASTM D-2047 (James Machine) >.6 Meets & Exceeds Passing Requirements
PACKAGING	5.38 sq.ft./tile; 26.91 sq.ft./carton; 968.76 sq.ft./pallet; 36 cartons/pallet; 20 pallets/container
COUNTRY OF MANUFACTURE	Korea