

STYLE NAME	Atmosphere Protec
COMPOSITION	Dual layer tile with homogeneous solid color top layer, composed with a two-part high pressure proprietary applied protective Shield+ coating. Backing layer non-vulcanized post-consumer recycled SBR (styrene butadiene rubber) or pre and post-consumer recycled regrind bound with a proprietary slow-cured MDI water based polymer.
SIZE	Straight Edge Tile: 38"x38" - 10.02 s/f per tile Interlocking Tile: 37"x37" - 9 .50 s/f per tile
THICKNESS	Standard backing 6mm (1 /4"), 8mm (5/16") and 10mm (3/8") High Density 8mm HD+ (heavy weight training)
FINISH	Matte
FLOORSCORE®	Certified SCS-FS-02937
ASTM D2047	Static Coefficient of Friction (James Machine method) Dry .96/ Wet 0.84
ASTM D3676	Density Foam Test Summary 53.8 lbs. /cu. ft.
ASTM D395B	Compression Set Under Force 2.4% recovered
ASTM E492	Tensile Strength 302.5 lb./sq. in.
ASTM-E648	Critical Radiant Flux passes (complete details available upon request through your To Market sales representative)
ASTM FL 37	Flexibility 6mm Mandrel Passes
ASTM F970-87	Static Load; .001 inch
ASTM G2 L	Mold Growth on Surface; no mildew after 28 days
CA 01350	VOC Emissions Section 01350 Passes
WARRANTY	10-year limited commercial warranty
MANUFACTURED	Canada