

STYLE NAME	Atmosphere Runway 2
PRODUCT LINE	Citation, Phenon, Falcon, Gulfstream, Global
COMPOSITION	Through-Body Color Tiles – 100% Post-Consumer Recycled Tire Rubber SBR (Styrene-Butadiene Rubber) + 100% PostIndustrial Colored EPDM (Ethylene-Propylene Diene Monomer) 2019 To Market Global proprietary combinations – AFTA Registered 2005
INSTALLATION	Straight Edge Tile / Rolls – Glue down Interlocking Tile – Loose Lay
SIZE	Straight Edge Tile – 23” x 23” Interlocking Tile – 21.75” x 21.75” Rolls – 4’ x 25’ or 4’ x 50’
THICKNESS	Straight Edge Tile / Rolls – 4 or 9mm Interlocking Tile – 9mm
CERTIFICATIONS	FloorScore®; ISO-9001 / ISO-14001
WARRANTY	10-Year Commercial
ABRASION & WEAR RESISTANCE	ASTM-D3390-05 / ASTM C501 – 0.73 g/loss
ACCELERATED TRAFFIC	ASTM-D6119-05 – Performance indicator 5 (no change)
ACOUSTIC RATING	ASTM-E989-06 / E492-96 4mm-IIC-57 / 9mm – IIC-59 (Impact Sound Transmission / Impact Insulation)
CHEMICAL RESISTANCE	ASTM-F925-97 – no change (surface dulling, staining attack, color change)
COEFFICIENT OF FRICTION	ASTM-D2047 – .85 dry / 1.01 wet
COMPRESSION	ASTM-D395-03 – 9.70% (compression set under constant force)
CRITICAL RADIANT FLUX	ASTM-E648 – Class 1 / Class 2
DENSITY (PCF)	ASTM-D3676 – 07 – 66 lbs / cubic foot
ELONGATION AT BREAK	ASTM-D412 – 06ae2 / 120%

(ATMOSPHERE
RUNWAY 2 COLLECTION)

REV. 9-30-22

CHEMICAL / STAIN RESISTANCE	ASTM-F925 No Change (ammonia, bleach, rust, grass, coffee, fruit juice, cola, ink, lipstick)
-----------------------------	--

CUSTOM	Custom colors, logo or graphic designs available
--------	--

COUNTRY OF MANUFACTURE	Made in the USA
------------------------	-----------------

FOR ADDITIONAL INFORMATION + PRODUCT SAMPLES, PLEASE CONTACT TO MARKET GLOBAL.