

PATTERN	Unicork 2
COMPOSITION	Bark of Cork Trees, a renewable and natural resource
INSTALLATION	Contact Cement
SIZE / PACKAGING	4.0 mm (floor): 23.63 x 11.82 (21.31 sq ft/pack) 5.0 mm (floor): 23.63 x 17.17 (5.81 sq ft/pack) 3.0 mm (wall): 23.63 x 11.82 (21.31 sq ft/pack)
WALL BASE	Small = 2 x 1/8 high x 3/8 thick x 46 7/8 long Tall = 3 1/2 high x 3/8 thick x 46 7/8 long
CUSTOMIZATION	19 stains colors available in 10 floor & 4 wall patterns
EDGE	Square edge (Beveled edge available for any pattern on 5mm)
FINISH	Available unfinished or unfinished with 3 coat lacquer (2 applied at plant, product, and tools for 1 additional field application supplied)
CERTIFICATIONS	FloorScore®; Mindful Materials
WARRANTY	10-Year Residential / 5-Year Commercial
DIMENSIONAL STABILITY	ASTM F2199 – passes Length .0012 per 12” (.10%) Width: less than .015 per 12” (.13%) Initial Curl: less than .03 / Final Curl: less than .14
SMOKE DENSITY	ASTM E-662-97 – passes <450 (NFPA 258)
LOAD LIMITS	Specified Load 250 psi; Residual Compression <.005 Specified Load 300 psi; Residual Compression <.006 Indentation – ASTM F1914 – passes Caster Chair Test – ISO 4918 – passes
SLIP RESISTANCE	ASTM -C1028-89 Exceeds .64 dry / Exceeds .47 wet
IMPACT SOUND INSULATION (IIC)	EN 15102:2007 (A1:201) – passes ASTM E492, IIC – passes
LEED	Credit 6 – Rapidly Renewable Material – 1 pt Credit 4.1 – Low Emitting Material – 1 pt Credit 4.4 – Environmental Quality – 1 pt
COUNTRY OF MANUFACTURE	Netherlands