

STYLE NAME	Urban 12
COMPOSITION	Virgin Vinyl - Phthalate Free
INSTALLATION	Glue down
SIZE	7.08" x 47.24"
GAUGE	2.0mm (0.080")
WEAR LAYER	12 mil
FINISH	Advanced Ceramic Bead Barrier + Coating No Wax, No Buff
CERTIFICATIONS	FloorScore®; Environmental Product Declaration (EPD); ISO-9001 / ISO-14001
WARRANTY	15-Year Residential / 8-Year Commercial
REFERENCE SPECIFICATIONS	ASTM F-1700 Solid Vinyl Floor Tile - Class III, Type B-Embossed Meets & Exceeds Passing Requirements for composition, size, thickness, squareness, flexibility, dimensional stability and resistance to chemicals.
RADIANT PANEL	ASTM E-648 Critical Radiant Flux - Class I Meets & Exceeds Passing Requirements
STATIC LOAD LIMIT	ASTM-F-970 Meets & Exceeds Passing Requirements
SLIP RESISTANCE	ASTM D-2047 (James Machine) >.6 Meets & Exceeds Passing Requirements
PACKAGING	2.32 sq.ft./plank; 41.85 sq.ft./carton; 2,513 sq.ft./pallet; 60 cartons/pallet; 20 pallets/container
COUNTRY OF MANUFACTURE	United States of America