

Rolled Goods Maintenance Instructions

TOMKT

TO MARKET



Initial Cleaning

- 1 Remove all loose debris by vacuuming, sweeping or by using a dust mop.
- 2 Wet scrub the floor by using a buffer or auto scrubber fitted with a soft nylon brush or 3M Blue Cleaner Pad 5300 or equivalent. The floor can also be cleaned by hand by using a microfiber mop head. We recommend using Diversey Profi Floor Cleaner and Grease Remover (product manufactured by Diversy – see notes) as a detergent for cleaning and maintenance but any neutral pH(7-9) is acceptable to use on the floor. Dilute the solution 10 oz. per gallon of water. Do not flood the floor with water.
- 3 Use a wet vacuum to pick up the cleaning solution from the floor and rise with clean water. Again, do not flood the floor. The rinse water should then be wet vacuumed from the floor.
- 4 Allow the floor to dry before foot traffic.

Regular Maintenance

- 1 Keep surface free from loose debris by sweeping, using a dust mop or by vacuuming the surface daily or as needed.
- 2 Damp mop surface by using a microfiber mop head or by using an auto scrubber fitted with a soft nylon brush. Use Diversey Profi Floor Cleaner and Grease Remover as the detergent and dilute 6-10 oz/ gallon water.

- 3 Use a wet vacuum to pick up the cleaning solution from the floor and rise with clean water. Again, do not flood the floor. The rinse water should then be wet vacuumed from the floor.
- 4 Allow the floor to dry before foot traffic.

Restorative Maintenance

- 1 Remove all loose debris by vacuuming, sweeping or by using a dust mop.
- 2 Scrub the floor by using an auto scrubber or buffer fitted with a 3M Black Stripper Pad 7200 or equivalent and using Taski Profi cleaner. Dilute to 10 oz per gallon of water. Keep the surface of the tiles wet to avoid damage to the tiles from the scrub pads. Do not flood the floor.
- 3 Use a wet vacuum to pick up the cleaning solution from the floor and rise with clean water. Again, do not flood the floor. The rinse water should then be wet vacuumed from the floor.
- 4 Allow the floor to dry before foot traffic.