

KP12Q1M



Date	_____
Project	_____
Location	_____

Commercial Code	KP12Q1M
Temperature range	+2/ +10°C
Technical features	<p>Display compartment in tempered glass throughout, externally screen-silk printed</p> <p>Built-in lower structure</p> <p>One refrigerated room</p> <p>Cooling unit at evaporation temperature -10 °C and condensation temperature 53,5°C rated at 1120 W</p> <p>Climate Class 4, room +30°C and 55% R.H.</p> <p>Ventilated refrigeration obtained through the evaporator being positioned in the lower part of the structure</p> <p>Relative humidity: 70%</p> <p>Automatic defrosting by air, every 6 hours, automatic evaporation of condense drain</p> <p>Ventilated system on the back with the air circulation not directed straight at food</p> <p>Refrigerant fluid: R404A</p> <p>Black glass electronic panel control board with touch keys and HACCP alarms (high/low temperature, probes failure, open door and black out)</p>
Functional features	<p>Softmotion pneumatic flapdoor opening system (140°) of the tempered glass open door</p> <p>Easily removable magnetic gasket</p> <p>Glass door with "invisible" full -height handle</p> <p>Supporting structure in PVC and glass; lower supporting structure in stainless steel</p> <p>Depth with open door: 107 cm</p> <p>Gross internal volume: 255 lt</p> <p>LED lighting (24 watt per led bar) for lower energy consumption and a letter light. LED bar positioned along the open door, not visible</p> <p>Installation allowed to an altitude up to 800 meters above sea level. For installation over 800, contact the company</p> <p>For combination of products, it is advisable to leave approximately 1,5 cm space</p> <p>Standard accessories: nr 2 tempered glass shelves (dimensions: 41 x 107 cm). Possibility of loading up to 20 kg per shelf</p> <p>Height adjustable feet.</p>
External size	120 x 66 x 115 h cm
Gross/Net weight	215/237kg
Electrical power	1 kW Standard connection: V-Hz 230V 1N-/60Hz

