

KP8QV - LUXOR WHITE



Date	_____
Project	_____
Location	_____

Commercial Code	KP8QV
Temperature range	+2/ +10°C
Technical features	<p>Display compartment in tempered glass throughout, with white screen-silk printed glass. With positive temperature models, special extra clear glazed tempered glass for increased brightness and display gloss</p> <p>Lower structure in extra clear white tempered glass</p> <p>One refrigerated room</p> <p>Cooling unit at evaporation temperature -10 °C and condensation temperature 53,5°C rated at 668 W</p> <p>Climate Class 4, room +30°C and 55% R.H.</p> <p>Ventilated refrigeration obtained through the evaporator being positioned in the lower part of the structure</p> <p>Relative humidity: 70%</p> <p>Automatic defrosting by air, every 6 hours, automatic evaporation of condense drain</p> <p>Ventilated system on the back with the air circulation not directed straight at food</p> <p>Refrigerant fluid: R404A</p> <p>Electronic panel control board with touch keys and HACCP alarms</p>
Functional features	<p>Display shelves in tempered glass. possibility of loading up to 12 kg per shelf.</p> <p>On request available the accessoire KSR25KGP: front bearing kit for shelves, to load up to 25 kg</p> <p>Easily removable magnetic gasket</p> <p>Glass door with “invisible” full-height handle</p> <p>Gross internal volume: 490 litri</p> <p>High brightness LED bar lighting, front panel on the back of the door and on internal ceiling element in the display compartment</p> <p>Installation allowed to an altitude up to 800 meters above sea level. For installation over 800, contact the company</p> <p>Standard accessories: nr 5 display shelves in tempered glass with the back upright on AISI 304 stainless steel rack</p> <p>Integrated wheels, hidden by the structure. (nr 4)</p>
External size	80.5x64.5x184cm
Gross/Net weight	222/247 kg
Electrical power	0.65 kW Standard connection: V-Hz 230V 1N-/60Hz

