

MODEL:
FAEMA E61 LEGEND 1grp
FAEMA E61 LEGEND 2grp

ITEM:
F01-A1112IIBT999A
F01-A1312IIBT999A

Date:

Project:

Location:

A PERFORMANCE
AND STYLE ICON.

E61 Legend



Semi-Automatic
dosed hot water and
beverage selections.

WHITE WOOD



CHROME



FEATURES



Temperature with
knobs



Built in volumetric
pump, two
pressure gauges



Adjustable thermal
balancing system
(Faema patent)



Hot water
wand

E61, THE STORY CONTINUES

It is 1961 and Faema writes an important page in its own history and in that of espresso coffee machines by introducing the E61.

Faema presents a new edition of its jewel. Though built maintaining the original design and materials, E61 features updated devices: an automatic boiler fill, a built in volumetric pump, two pressure gauges, to control the pump and the boiler pressure, and the adjustable thermal balancing system (FAEMA patent). E61 Jubile, features dosed hot water and beverage selections.

Why is it so special

E61 is the first machine to use a volumetric pump to give the water the ideal 9-atmosphere pressure and keep the pressure constant during the whole extraction process, unlike lever machines. Furthermore, thanks to the preinfusion system, the extension of the contact time between the water and the ground coffee before extraction favours optimal extraction when it comes to the organoleptic properties of the espresso.

The shape of the myth

Though built maintaining the original design and materials, E61 features updated devices linked to its revolutionary technical solutions and its stainless steel elegant body.

Innovative technical solutions, pure steel body
work and elegant back- illuminated glass design.





1 Group



2 Group



3 Group



Semi-Automatic, dosed hot water and beverage selections.

		E61 - LEGEND		
		1	2	3
Features				
Steam wands		2	2	2
Hot water wands		1	1	1
Hot water selections		-	-	-
Boiler capacity (L)		6	11	17.5
Electric cup warmer (3-temp settings)		-	-	-
Technical Information				
Dimensions:	W x Dx H (mm)	550 x 540 x 565	715 x 540 x 565	955 x 540 x 565
Weight (kg)		51	60	80
Power at	220-240V~ 60Hz (W) 220-240V3~ 60Hz (W)	3300-3900	4000-4800	4800-5700

Water & Drain Line Requirements

Cold Water Line:

3/8" dedicated cold water line with shut-off valve, compression fitting and back flow preventer.

Drain:

Open gravity drain of minimum 1.25" ID size for hose, within 4 feet of machine.

Water Flow:

Minimum incoming water flow rate of 35 GPH and maximum line pressure 70PSI/ 5 Bar. Should flow pressure exceed 70 PSI a pressure reducer is necessary.

Access Hole:

There must be a 2 1/2" access hole underneath the machine to connect the water, drain and power supply.



E61 Legend

A1 - Group

A2 - Group

Receptacle



NEMA 6-20R

Receptacle



NEMA L6-30R

FAEMA Canada reserves the right to modify the characteristics of the products illustrated in this publication without prior notice for misprints and other errors. There may be colour deviations due to the printing process.