



**Product:** [8723](#)

Audio, Control & Instrument, #22-2pr, PO, Individ. Foil, PVC Jkt, CM

### Product Description

Audio, Control & Instrument Cable, 22 AWG stranded (7x30) tinned copper conductors, polypropylene insulation, twisted pairs, individually Beldfoil® shielded (100% coverage), 24 AWG stranded tinned copper drain wire, PVC jacket.

### Technical Specifications

#### Product Overview

|                        |   |
|------------------------|---|
| Suitable Applications: | low voltage analog signals (4-20ma, 0-10v, ...); low voltage digital control (24v, ...); line level audio; computer communication; panel wiring |
|------------------------|---|

#### Construction Details

##### Conductor

| Element | Number of Element | Size   | Stranding | Material           |
|---------|-------------------|--------|-----------|--------------------|
| Pair(s) | 2                 | 22 AWG | 7x30      | TC - Tinned Copper |

##### Insulation

| Element | Material           | Nom. Thickness     | Nom. Insulation Diameter | Color Code                 |
|---------|--------------------|--------------------|--------------------------|----------------------------|
| Pair(s) | PP - Polypropylene | 0.009 in (0.23 mm) | 0.046 in (1.2 mm)        | Black & Red, Green & White |

##### Inner Shield

| Element | Shield Type | Material                | Coverage | Drainwire Type   | Notes                                      |
|---------|-------------|-------------------------|----------|------------------|--|
| Pair(s) | Tape        | Bi-Laminate (Alum+Poly) | 100%     | 24 AWG (7x32) TC | foil-out tape on each pair, one drain wire |

##### Outer Jacket

| Material                 | Nom. Thickness     | Nom. Diameter      |
|--------------------------|--------------------|--------------------|
| PVC - Polyvinyl Chloride | 0.020 in (0.51 mm) | 0.160 in (4.06 mm) |

|                                   |                    |
|-----------------------------------|--------------------|
| Overall Cable Diameter (Nominal): | 0.160 in (4.06 mm) |
|-----------------------------------|--------------------|

#### Electrical Characteristics

##### Electricals

| Element | Nom. Conductor DCR | Nom. Inner Shield DCR           | Nom. Capacitance Cond-to-Cond | Nom. Capacitance Cond-to-Other (Conds + Shield) | Nom. Characteristic Impedance | Nom. Velocity of Prop. | Max. Current                   |
|---------|--------------------|---------------------------------|-------------------------------|---|-------------------------------|------------------------|--------------------------------|
| Pair(s) | 18.2 Ohm/1000ft    | 18.38 Ohm/1000ft (60.30 Ohm/km) | 33 pF/ft (110 pF/m)           | 62 pF/ft (200 pF/m)                             | 52 Ohm                        | 66%                    | 2.8 Amps per Conductor at 25°C |

##### Voltage

|                          |
|--------------------------|
| <b>UL Voltage Rating</b> |
| 300 V (CM)               |

#### Mechanical Characteristics

##### Temperature

| UL Temperature | Operating      |
|----------------|----------------|
| 60°C           | -20°C to +75°C |

##### Bend Radius

| Stationary Min. | Installation Min. |
|-----------------|-------------------|
|                 |                   |

1.6 in (41 mm) 1.6 in (41 mm)

|                    |                |
|--------------------|----------------|
| Max. Pull Tension: | 42 lbs (19 kg) |
| Bulk Cable Weight: | 17 lbs/1000ft  |

## Standards and Compliance

|                                  |   |
|----------------------------------|---|
| Environmental Suitability:       | Indoor  |
| Flammability / Reaction to Fire: | UL 1685 FT4 Loading, IEC 60332-1-2  |
| CPR Compliance:                  | CPR Euroclass: Eca; CPR UKCA Class: Eca   |
| NEC / UL Compliance:             | Article 800, CM   |
| CEC / C(UL) Compliance:          | CM  |
| European Directive Compliance:   | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| UK Regulation Compliance:        | UKCA Mark   |
| APAC Compliance:                 | China RoHS II (GB/T 26572-2011)   |
| Plenum Number:                   | 82723, 87723, 88723   |

## History

|                      |  |
|----------------------|--|
| Update and Revision: | Revision Number: 0.572 Revision Date: 04-19-2023 |
|----------------------|--|

## Part Numbers

### Variants

| Item #        | Color  | Putup Type | Length    | UPC/EAN       |
|---------------|--------|------------|-----------|---------------|
| 8723.0030     | Chrome | Reel       | 30 m      | 8719605018571 |
| 8723.060100   | Chrome | Reel       | 100 ft    | 612825214441  |
| 8723.00100    | Chrome | Reel       | 100 m     | 8719605159229 |
| 8723.00U152   | Chrome | UnReel     | 152 m     | 8719605018588 |
| 8723.01152    | Chrome | Reel       | 152 m     | 8719605018601 |
| 8723.00U305   | Chrome | UnReel     | 305 m     | 8719605018595 |
| 8723.01305    | Chrome | Reel       | 305 m     | 8719605018632 |
| 8723.060500   | Chrome | Reel       | 500 ft    | 612825214526  |
| 8723.060U500  | Chrome | UnReel     | 500 ft    | 612825214434  |
| 8723.02500    | Chrome | Reel       | 500 m     | 8719605018663 |
| 8723.01610    | Chrome | Reel       | 610 m     | 8719605018656 |
| 8723.0601000  | Chrome | Reel       | 1,000 ft  | 612825214458  |
| 8723.060U1000 | Chrome | UnReel     | 1,000 ft  | 612825214410  |
| 8723.001000   | Chrome | Reel       | 1,000 m   | 8719605018564 |
| 8723.011524   | Chrome | Reel       | 1,524 m   | 8719605018618 |
| 8723.0601640  | Chrome | Reel       | 1,640 ft  | 612825214496  |
| 8723.0602000  | Chrome | Reel       | 2,000 ft  | 612825214502  |
| 8723.060U2000 | Chrome | Reel       | 2,000 ft  | 612825214427  |
| 8723.013048   | Chrome | Reel       | 3,048 m   | 8719605018625 |
| 8723.013050   | Chrome | Reel       | 3,050 m   | 8719605018649 |
| 8723.0603280  | Chrome | Reel       | 3,280 ft  | 612825214519  |
| 8723.0605000  | Chrome | Reel       | 5,000 ft  | 612825214533  |
| 8723.06010000 | Chrome | Reel       | 10,000 ft | 612825214465  |
| 8723.06010001 | Chrome | Reel       | 10,000 ft | 612825214472  |
| 8723.0609999  | Chrome | Reel       | 10,000 ft | 612825214540  |
| 8723.06015000 | Chrome | Reel       | 15,000 ft | 612825214489  |

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.