



WOOD WAX FINISH

Transparent and intensive colour designs!



PRODUCT DESCRIPTION

Transparent or intensive coloured wood finish that uniquely combines the advantages of natural oils and waxes in one product. Osmo Wood Wax Finish is stain-resistant, water-repellent and abrasion-resistant and results in a surface that is pleasant to the touch. In comparison to conventional finishes, the use of plant ingredients creates a more even colour and more harmonious appearance.

Simple application – without primer or intermediate sanding – this saves time and money.

Suitable for wood, microporous, will not crack, peel, flake or blister. Resistant to wine, beer, cola, tea, fruit juice, milk and water acc. German DIN 68861-1C – no water spots.

The dry finish is safe for humans, animals and plants (resistant to saliva and perspiration acc. German DIN 53160, suitable for children's toys acc. EN 71.3).

RECOMMENDED USE

Osmo Wood Wax Finish is suitable for the protection and the decorative finishing of wood in indoor areas: wall panelling, mouldings and beams as well as doors. It is also suitable for edge-glued panels, chipboard

and MDF. Ideal as a coloured base coat for wooden flooring and for recoating darkened wood surfaces. Highly recommended for furniture and children's toys.

INGREDIENTS

Based on natural plant oils and waxes (sunflower oil, soya oil, thistle oil, carnauba wax and candelilla wax), paraffin, iron oxide and organic pigments, titanium dioxide white pigment, siccatives (drying agents) and water-repelling additives. Dearomatized white spirit (benzene-free), EU limit value for this product (cat. A/e): 400 g/l VOC (2010). This product contains max. 400 g/l VOC. Detailed declaration of ingredients available upon request.

TECHNICAL DATA

Specific weight: 0.90 -1.3 g/cm³
 Viscosity: >70s DIN EN ISO 2431/3 mm, viscid
 Odour: faint/mild, odourless after drying
 Flash point: >61 °C, acc. DIN EN ISO 2719



STORAGE

Up to 5 years and longer if can is kept dry and closed tightly. If thickened by frost, store for 24 - 36 hours at room temperature before use.

SURFACE PREPARATION

The wood surface must be clean, dry and frost-free (max. 18% moisture content). Osmo Wood Wax Finish is ready to use. Do not thin. Stir well before use.

Clean old microporous stains thoroughly. Old paints and lacquers must be completely removed. As a general rule, wear a dust mask during sanding works. Fill small cracks, larger joints or holes in wood (with Osmo Wood Filler).

Sand wood surface carefully, begin with coarse sandpaper – final sanding work for flooring P120-150, for furniture P220-240.

Before applying oils, remove sanding dust from the surface by sweeping or vacuuming.

If possible, please apply the first coat to all sides before installation.

The finished surface is influenced by several factors, including the condition of the wood. Therefore, a trial application is always required, especially for unfamiliar surfaces.

METHODS OF APPLICATION

Transparent colour (one coat): with Osmo Flat Brush, Oil Finish Applicator Fleece (Hand Pad Holder) or Microfibre Roller, apply very thinly to the clean and dry wood surface along the wood grain and spread well.

For a more subtle stained effect, apply thinly with a lint-free cloth and within 20 minutes, wipe away cleanly and evenly. Ventilate well while drying.

Intensive colour (two coats): with Osmo Flat Brush or Microfibre Roller, apply very thinly to the clean and dry wood surface along the wood grain and spread well. Ventilate well while drying. Apply the second coat - also thinly.

Note: Larger areas can also be coated by using a scraper. Afterwards rub in with a white pad.

Important: For mechanically loaded areas, e.g. flooring, we recommend max. one coat and generally a thin top coat with clear Osmo Polyx®-Oil Original. For white flooring, a top coat with lightly white pigmented Osmo Polyx®-Oil Tints 3040 White.

In general, intensive colour applications (two coloured coats) are not recommended for flooring due to the risk of applying too much product.

CLEANING OF TOOLS

With Osmo Brush Cleaner (free of aromatic compounds).

DRYING TIME

Approx. 24 hours (normal climatic conditions, 23 °C/ 50 % rel. humidity). Lower temperatures and/or higher air humidity can increase the drying time. Ventilate well while drying.

COVERAGE

1 litre covers approx. 24 m² with one coat.

Coverage depends significantly on the condition of the wood. All information refers to smooth and planed/sanded surfaces. Other surfaces may lead to differences in coverage.

NOTE

Applying the product too generously and insufficient ventilation lead to delays in drying time and the typical smell of oil.

Choose colour tones that match the natural tone of wood or a darker colour tone (trial application).

Oils enhance the natural colour tone of wood (permanent wet effect).

For dark and extractive-rich hardwoods (e.g. Wenge, Mahogany, Merbau etc.), we recommend applying Osmo Wood Wax Finish Clear Extra Thin. Trial application is recommended.

Caution: Apply max. one coat thinly to cabinet interiors and drawers with a cloth.

CAUTION

Keep out of the reach of children. Do not get in eyes, on skin, or on clothing. If medical advice is needed, have product container or label at hand. Use only outdoors or in a well-ventilated area. Warning: Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition). The dried finish is classified as B2 (normal flammability) according to DIN 4102 regulations. Safety data sheet available on request.

DISPOSAL

Dispose of leftover product and completely emptied packaging according to local official guidelines (waste code number 08 01 11). Only completely emptied cans can be recycled.



COLOUR TONES

- 3101 Clear
- 3102 Lightly Steamed Beech
- 3103 Light Oak
- 3104 Red
- 3105 Yellow
- 3111 White
- 3118 Granite Grey
- 3119 Silk Grey
- 3123 Pine
- 3125 Blue
- 3131 Green
- 3132 Grey Beige
- 3136 Birch
- 3137 Cherry
- 3138 Mahogany
- 3143 Cognac
- 3161 Ebony
- 3164 Oak
- 3166 Walnut
- 3168 Oak Antique
- 3169 Black
- 3172 Silk
- 3181 Pebble
- 3186 White Matt
- 3188 Snow

CAN SIZES (DEPENDING ON PRODUCT)

0.125 L; 0.375 L; 0.75 L; 2.50 L; 25 L

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 02/17