

A22PCMCW

TECHNICAL DATA SHEET

22mil PolyCotton Instant Dry MATTE Canvas - Water

Description:

Exceptional quality 35/65 canvas for the most discerning printer. Compare it to any competitive matte canvas and you will find our canvas is truly OBA Free and acid neutral which translates to true archival quality. The matte coating accepts heavy ink loads for rich color gamut, true blacks and skin tones. Finish it with liquid laminate for a crack free gallery wrap.

Specifications:

Weight: 420gsmBasis Caliper: 21mil

Opacity: 96%Brightness: 82Whiteness: 79

Finish: Matte water fast coating

Ink Compatibility: Aqueous, Latex and UV

Laminate Compatibility: Liquid Laminate Recommended

Core Size: 3" w/ 2" Adapter

Storage:

Store in a controlled environment, approximately 70°F (21°C) +/-10°F and 50% RH +/- 10%, free from dust and direct sunlight in original packaging until ready for use. Shelf life 12-15 months under these conditions. After printing return unused media to original polyester bag/packaging for storage.

Printing:

For best performance, print in a controlled environment approximately 70°F/21°C with 35-65% relative humidity. As with all inkjet media, handle media at the edges to avoid touching the imaging area as fingerprints and oils from hands can repel ink causing poor image quality. We recommend calibrating the media for optimum quality. Actual results can vary depending on proper ink limitation, printer/rip settings and color management used. Allow prints to dry for at least 30 minutes. Drying time may vary depending on printer, inks, amount of ink used and environmental conditions (images with heavy ink coverage may require a longer drying time).

Finishing:

Liquid laminate highly recommended to eliminate cracking when stretch mounting. Lamination can provide an enhanced finish and extended print life through protection from dirt, abrasion and ink fading from UV exposure. Allow print to completely dry prior to laminating.

2903 Saturn St; Unit G Brea, Ca 92821 800-345-8944