

Description:

These 4mil pressure sensitive lamination films are used to enhance and protect digital inkjet and photographic images. Available in gloss, lustre and matte finishes, these over laminates are comprised of a crystal clear PCV film coated with an optically clear acrylic adhesive, which eliminates problems such as imaging silvering and mottling during application. UV inhibitors are built into both the PCV film and acrylic adhesive to resist image fading due to prolonged UV-light exposure.

Specifications:

- Face Stock Weight: 105gsm
- Face Stock Caliper: 4mil
- Face Stock Material: Clear PVC Film
- Face Stock Finish: Luster
- Liner Weight: 80gsm
- Liner Caliper: 4mil
- Liner Material: Kraft Paper
- Adhesive: Pressure Sensitive Solvent Acrylic - Permanent

Storage:

Store in a controlled environment, (approximately 60°F-80°F +/-10°F and 65% RH +/- 10%) free from dust and direct sunlight in original packaging until ready for use. Shelf life 18-24 Months under these conditions. After use, return unused media to original polyester Bag/package for storage.

Application & Handling:

Apply lamination at room temperature. If a top heated roller is available, set roller temperature to 90°F-100°F. Heat can assist the lamination process by activating the adhesive and shortening the adhesive curing time. After applying the laminate, allow graphic to lay flat for a minimum of two hours of cure time before cutting, trimming or rolling. Ideally, the laminated graphics should be allowed to cure for 24 hours.

Once applied and cured, laminates are not designed to be removed and reapplied. This lamination film is washable and resistant to many detergents.