

Description:

This 8mil PVC textured laminate was specially designed to be a protective overlay for any vinyl or polypropylene with adhesive to create a temporary floor advertisement. It allows for direct printed floor graphics. UL rated (UL410) for anti-slip properties. Formulated solvent acrylic adhesive make for a strong bond and exceptional clarity. Some inks may contain excessive flow additives that can reduce adhesion so test before production.

Specifications:

- Face Stock Weight: 200gsm
- Face Stock Caliper: 8mil
- Face Stock Material: Clear PVC Film
- Face Stock Finish: Textured Matte
- Liner Weight: 80gsm
- Liner Caliper: 4mil
- Liner Material: Kraft Paper
- Adhesive: Pressure Sensitive Solvent Acrylic - Permanent

Storage:

Store in a controlled environment, (approximately 60°F-80°F +/-10°F and 65% RH +/- 10%) free from dust and direct sunlight in original packaging until ready for use. Shelf life 18-24 Months under these conditions. After use, return unused media to original polyester Bag/package for storage.

Application & Handling:

Apply lamination at room temperature. If a top heated roller is available, set roller temperature to 90°F-100°F. Heat can assist the lamination process by activating the adhesive and shortening the adhesive curing time. After applying the laminate, allow graphic to lay flat for a minimum of two hours of cure time before cutting, trimming or rolling. Ideally, the laminated graphics should be allowed to cure for 24 hours.

Once applied and cured, laminates are not designed to be removed and reapplied. This lamination film is washable and resistant to many detergents.