

SLU007

TECHICAL DATA SHEET 14

14mil Satin Semi-Rigid Grey Backed Hybrid Film

Description:

This hybrid semi rigid film offers the durability and stability of PET film along with the economical price of polypropylene. It features the preferred white back and stay flatness required for good looking banner stand displays. This block out display film lays flat with no cupping and is ultra-durable. The high white point give bright graphics. Applications: Roll-up banner stands, Pop-in displays units, Interior window displays and POP advertising.

Specifications:

Weight: 190gsm
Basis Caliper: 10mil
Opacity: 100%
Whiteness: 102
Gloss (@60°): 18
Finish: Satin

Ink Compatibility: Solvent / Eco-Sol / Latex / UV
 Laminate Compatibility: Pressure sensitive

Storage:

Store in a controlled environment, approximately $70^{\circ}F$ ($21^{\circ}C$) +/- $10^{\circ}F$ and 50% RH +/- 10%, free from dust and direct sunlight in original packaging until ready for use. Shelf life 12-15 months under these conditions. After printing return unused media to original polyester bag/packaging for storage.

Printing:

For best performance, print in a controlled environment approximately 70°F/21°C with 35-65% relative humidity. As with all inkjet media, handle media at the edges to avoid touching the imaging area as fingerprints and oils from hands can repel ink causing poor image quality. We recommend calibrating the media for optimum quality. Actual results can vary depending on proper ink limitation, printer/rip settings and color management used.

Finishing:

This product is compatible with pressure sensitive lamination films. Laminating graphics is always recommended as it will provide better protection against abrasion, pollution and UV rays and will add to the overall durability to material. Finished graphics should be wound with a minimum inner diameter of 6". This will prevent the image from tunneling.