

## Description:

This 5mil gloss adhesive back vinyl is the best option for everyday printing. With its bright white surface for the brightest color graphics and it's improved double sided PE coated liner for easy installations as well as the solvent acrylic adhesive for long term adhesion, this vinyl will be your go to for most of you mounting jobs. Economically priced to keep you square foot price down. Applications: Floor graphics, flexible signage, mounted signage and trade show graphics. Compatible with Solvent, Eco-Sol, latex and UV ink systems.

## Specifications:

- Basis Caliper: 4.5mil
- Face Stock Weight: 165gsm
- Gloss @ 60: 28
- Release Liner: 6mil
- Finish: Gloss
- Ink Compatibility: Ink Compatibility: Solvent / Eco-Solvent / Latex / UV
- Laminate Compatibility: Pressure sensitive and liquid laminates

## Storage:

Store in a controlled environment, approximately 70°F (21°C) +/-10°F and 50% RH +/- 10%, free from dust and direct sunlight in original packaging until ready for use. Shelf life 12-15 months under these conditions. After printing return unused media to original polyester bag/package for storage.

## Printing:

For best performance, print in a controlled environment approximately 70°F/21°C with 35-65% relative humidity. As with all inkjet media, handle media at the edges to avoid touching the imaging area as fingerprints and oils from hands can repel ink causing poor image quality. We recommend calibrating the media for optimum quality. Actual results can vary depending on proper ink limitation, printer/rip settings and color management used. Allow prints to dry for at least 30 minutes. Drying time may vary depending on printer, inks, amount of ink used and environmental conditions (images with heavy ink coverage may require a longer drying time).

## Finishing:

This product is compatible with pressure sensitive lamination films as well as liquid laminations. Laminating graphics is always recommended as it will provide better protection against abrasion, pollution and UV rays and will add to the overall durability to the material. Finished graphics should be wound with a minimum inner diameter of 6". This will prevent the image from tunneling during transport. Application surface should be flat or only simple curves. Please make sure the surface and surrounding area are properly cleaned and free of contaminants