

TECHICAL DATA SHEET

SLU019

21mil PolyCotton Satin Canvas

Description:

A 21mil stretchable crack resistant Oxford 2 over 1 canvas that is a 65% polyester/35% cotton blend. Unlike most solvent canvas products, this canvas provides a consistent satin printing surface that allow for extremely wide color gamut, rich black densities, while still offering the traditional artist's texture look and feel. This canvas achieves amazing color accuracy and ink saturation even at full production print speed for high volume printing environments. Print makers can choose to apply water based laminates for added durability and crack resistance however lamination is not required.

Specifications:

Weight: 370gsmBasis Caliper: 21mil

Opacity: 97%Brightness: 81Whiteness: 71Finish: Satin

Ink Compatibility: Solvent/Eco-Sol/Latex/UVLaminate Compatibility: Not Required

Storage:

Store in a controlled environment, approximately $70^{\circ}F$ ($21^{\circ}C$) +/- $10^{\circ}F$ and 50% RH +/- 10%, free from dust and direct sunlight in original packaging until ready for use. Shelf life 12-15 months under these conditions. After printing return unused media to original polyester bag/packaging for storage.

Printing:

For best performance, print in a controlled environment approximately 70°F/21°C with 35-65% relative humidity. As with all inkjet media, handle media at the edges to avoid touching the imaging area as fingerprints and oils from hands can repel ink causing poor image quality. We recommend calibrating the media for optimum quality. Actual results can vary depending on proper ink limitation, printer/rip settings and color management used. Allow prints to dry for at least 30 minutes. Drying time may vary depending on printer, inks, amount of ink used and environmental conditions (images with heavy ink coverage may require a longer drying time).

Finishing:

Compatible with liquid laminates. Lamination can provide an enhanced finish and extended print life through protection from dirt, abrasion, and ink fading from UV exposure. Allow print to completely dry prior to laminating.

2903 Saturn St; Unit G Brea, Ca 92821 800-345-4-8944