

Description:

This 5mil clear, transparent polyester film for eco-solvent, solvent and UV curable inks. The main advantages are the high contrast and excellent color gradation. The film is anti-static and heat stable, always ensuring perfect flatness without the need of a sensor strip. Perfect for your screen printing needs. Applications: POP, Poster, Window Display, Presentation, GIS/ Mapping and Screen Printing.

Specifications:

- Weight: 170gsm
- Basis Caliper: 5.2mil
- Opacity: NA
- Brightness: NA
- Whiteness: NA
- Finish: Clear Resin Coating
- Ink Compatibility: Solvent/Eco-Sol/Latex/UV
- Laminate Compatibility: Cold Pressure Sensitive

Storage:

Store in a controlled environment, approximately 70°F (21°C) +/-10°F and 50% RH +/- 10%, free from dust and direct sunlight in original packaging until ready for use. Shelf life 12-15 months under these conditions. After printing return unused media to original polyester bag/package for storage.

Printing:

For best performance, print in a controlled environment approximately 70°F/21°C with 35-65% relative humidity. As with all inkjet media, handle media at the edges to avoid touching the imaging area as fingerprints and oils from hands can repel ink causing poor image quality. We recommend calibrating the media for optimum quality. Actual results can vary depending on proper ink limitation, printer/rip settings and color management used. Allow prints to dry for at least 30 minutes. Drying time may vary depending on printer, inks, amount of ink used and environmental conditions (images with heavy ink coverage may require a longer drying time).

Finishing:

Compatible pressure sensitive lamination films. Lamination can provide an enhanced finish and extended print life through protection from dirt, abrasion, and ink fading from UV exposure. Allow print to completely dry prior to laminating. When preparing a laminated print for transport, roll the print image side out and as loose as possible to avoid tunneling.