

Description:

A 7.5mil static cling clear non-top coated glossy PVC vinyl. Designed for window decals, temporary product markings, point of purchase displays and protective masking. The highly plasticized vinyl film is designed to adhere to most clean, smooth surfaces. Compatible with most solvent and UV curable printers.

Specifications:

- Weight: NA
- Basis Caliper: 7.5mil
- Opacity: NA
- Gloss (@60°): NA
- Finish: Glossy
- Ink Compatibility: Solvent / Eco-Sol / UV
- Laminate Compatibility: Pressure sensitive and Liquid Laminates

Storage:

Store in a controlled environment, approximately 70°F (21°C) +/-10°F and 50% RH +/- 10%, free from dust and direct sunlight in original packaging until ready for use. Shelf life 12-15 months under these conditions. After printing return unused media to original polyester bag/package for storage.

Printing:

For best performance, print in a controlled environment approximately 70°F/21°C with 35-65% relative humidity. As with all inkjet media, handle media at the edges to avoid touching the imaging area as fingerprints and oils from hands can repel ink causing poor image quality. We recommend calibrating the media for optimum quality. Actual results can vary depending on proper ink limitation, printer/rip settings and color management used.

Finishing:

This product is compatible with pressure sensitive lamination films as well as liquid laminations. Laminating Graphics is always recommended as it will provide better protection against abrasion, pollution and UV rays and will add to the overall durability to the material. Finished graphics should be wound with a minimum inner diameter of 6". This will prevent the image from tunneling.