

参数规格

型号: JA401		启动电压: 12V
启动电流: 2000A	峰值电流: 3750A	充气压力范围: 10~150 PSI
输入: USB-C 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3A (60W MAX)	输出: USB-A 5V/3A, 9V/2A, 12V/1.5A (18W MAX) USB-C 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3A (60W MAX)	
充电温度: 0°C~45°C	工作温度: -20°C~50°C	
存储温度: -20°C~50°C	充满电时间: ≤1.5 小时	
使用寿命: >1000 cycles (在保养良好的情况下)		

包装清单

主机	点火夹	充气管	转换头
			
产品收纳袋	配件收纳袋	使用说明书	USB-C线
			

简要介绍

1. 12V发动机的应急启动电源 (12V汽油≤10.0升、12V柴油≤8.0升)
2. 内置充气泵, 支持胎压检测、预设充停、单位切换等功能、气压检测精度±2 PSI、最大打气压力150 PSI;
3. LED灯照明 (光通量400 LUMENS、SOS/频闪/常亮模式切换);
4. 充电: USB-C (5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3A (60W MAX));
5. 放电: USB-A (USB-A 5V/3A, 9V/2A, 12V/1.5A (18W MAX))
USB-C 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3A (60W MAX)



LOKITHOR

JA401











The Force of Thunder in Hand

Parameter Specification


Product Model: JA401	
Starting Voltage: 12V	Peak Current: 2000A
Pressure Range: 10~150 PSI	Starting Current: 3750A
Input:USB-C 5V/3A,9V/3A,12V/3A,15V/3A,20V/3A(60W MAX)	Output: USB-A 5V/3A,9V/2A,12V/1.5A(18W MAX) USB-C 5V/3A,9V/3A,12V/3A,15V/3A,20V/3A(60W MAX)
Operating Temp: -20°C to 50°C	Charging Temp: 0°C to 45°C
Storage Temp: -20°C to 50°C	Charging Time: ≤1.0 Hours
Service life: >1000 cycles(in good condition)	

Packing List

Multi-function vehicle emergency starter	LO-CLAMP-Pro	Inflatable hose	Nozzle adapters
			1.Presta Valve Adaptor 2.Inflatable Nozzles 3.Ball Needle 
Product storage bag	Accessories storage bag	Manual	USB-C cable
			

Product Overview

- Emergency start of 12V engine (up to 10.0-Liter gasoline and 8.0-Liter diesel 12 V engines)
- Built-in air inflator, support tire pressure detection, preset charging and stopping value, unit switching and other functions; Air pressure sensor accuracy: ±2 PSI, maximum inflation pressure 150 PSI;
- LED lighting (luminous flux: 400 LUMENS, 3modes: SOS/stroboscopic/constant light)
- Charging: USB-C 5V/3A,9V/3A,12V/3A,15V/3A,20V/3A(60W MAX)
- Discharging: USB-A 5V/3A,9V/2A,12V/1.5A(18W MAX)
USB-C 5V/3A,9V/3A,12V/3A,15V/3A,20V/3A(60W MAX)



Spezifikationen

Model: JA401	
Start Spannung: 12V	Start Strom: 2000A
Druckbereich Kompressor: 10~150 PSI	Spitzenstrom: 3750A
Output: USB-A 5V/3A,9V/2A,12V/1.5A(18W MAX) USB-C 5V/3A,9V/3A,12V/3A,15V/3A,20V/3A(60W MAX)	Input:USB-C 5V/3A,9V/3A,12V/3A,15V/3A,20V/3A(60W MAX)
Arbeitstemperatur: -20°C bis 50°C	Ladetemperatur: 0°C bis 45°C
Lagertemperatur: -20°C bis 50°C	Ladezeit: ≤1.0 Stunden
Lebensdauer: >1000 Zyklen (Bei Einhaltung der Vorgaben und Pflegemaßnahmen)	

Packing List

Multifunktionales Starthilfegerät	Startklammern	Luftschlauch	Adapterdüsen
			1.Ventiladapter 2.Konische aufblasbare Düsen 3.Nadeladapter 
Transporttasche	Schutzhülle	Bedienungsanleitung	USB-C Kabel
			

Anwendungsgebiet

- Starthilfegerät für 12V Motoren (startet 12V Motoren mit 10.0L Hubraum (Benzin und 8,0L Hubraum (Diesel))
- Eingebauter Kompressor zur Anpassung und Kontrolle des Reifendrucks.
Überprüfung des aktuellen Drucks , Druckvorwahl, Einheiten Vorwahl (PSI / BAR) und weitere Funktionen; Präzision des eingebauten Druckmessers: ±2 PSI, maximaler Reifendruck150 PSI;
- LED Licht (Lichtstrom: 400 LUMEN, 3 Modi: SOS / Stroboskop / Konstant Licht)
- Laden: USB-C 5V/3A,9V/3A,12V/3A,15V/3A,20V/3A(60W MAX)
- Entladeausgänge: USB-A 5V/3A,9V/2A,12V/1.5A(18W MAX)
USB-C 5V/3A,9V/3A,12V/3A,15V/3A,20V/3A(60W MAX)

