






NOTE:ALL MATERIAL COMPLIANT ROHS STANDARD

REVISION INFORMATION			
Rev.	Rev. Date	Modified By	Brief Description
1.0	2016/04/28	Pillar	Add labels on packaging
2.0	2016/09/09	Pillar	Change Molding
3.0	2017/08/21	Ndq	Add one bag to the packing

Electrical character:

- 1)100% Open/short/Intermittent testing
- 2)Withstanding voltage:DC/AC 300V AT 10ms.
- 3)Insulation resistance:10M Ohm(min)
- 4)Conductive resistance:2 Ohm




PIN ASSIGNMENT

HDMI A F	HDMI A M
3	3
1	1
2	2
6	6
4	4
5	5
9	9
7	7
8	8
12	12
10	10
11	11
19	19
14	14
17	17
13	13
15	15
16	16
18	18
SHELL	SHELL

①	PCBA	HDMI A Male to Female PCBA		
②	Conn	HDMI A Male,Pin G/F,Black Insulation,Shell/Steel(Gold Plated)		
③	Conn	HDMI A Female,Pin G/F,Black Insulation,Shell/Steel(Gold Plated)		
④	Innermold	PE,Low density		
⑤	Overmold	PVC,45Pa,Black		
NO.	PART NAME	SPECIFICATION DESCRIPTION	QTY	UNIT

Unless specified on the drawing, tolerances are per the follows:

.	+1
.x	+0.2
.xx	+0.05



BigCatCables

DRAWN BY	DATE: 2017/08/21	DESCRIPTION: HDMI Male-Female 90 degree Adapter
CHECKED BY	SHEET 1 of 2	ITEM NO. BC-0901-B
APPROVED BY	SCALE None	REV. 3.0 UNIT:mm

