

GRITTER TYPE SH



SH with tarpaulin

	Funnel volume approx. in l	Max. gritting range in m	Min. oil consumption in l/min	Max. output in l/min	Load capacity in kg	Weight in kg
SH	265	9	15	80	500	115

Suitable for salt, sand and grit

- driven by the forklift hydraulic system
- variable gritting range; can be adjusted by varying height and angle of inclination of mast
- stirring mechanism
- protective grating
- fork sleeves for pick-up by a forklift truck
- spray painted **RAL 2000**

Accessories

- tarpaulin

Fork sleeve inside dimensions in mm			
c			
	A	B	C
SH	670	200	70

SPREADER TYPE STW



STW 100 with tarpaulin



STW 260

Suitable for salt and sand

- can be towed by a forklift truck or small traction engine etc.
- with solid rubber tyres (type STW 100) or with pneumatic tyres (type STW 260)
- wheel motion activates spread
- with lever to adjust spreading width and direction
- funnel spray painted **RAL 3000**

Accessories

- tarpaulin



Snowblower SCH-G with an STW 100

	Funnel volume approx. in l	Finish funnel	Max. gritting range in m	Load capacity in kg	Weight in kg
STW 100	105	paint	6	135	28
STW 260	260	paint	12	340	84