Revision Date: 04/16/2021

SAFETY DATA SHEET

Classified in accordance 29 CFR 1910.1200

1. Identification

Product identifier: ULTIMATE ADHESIVE SPRAY

Other means of identification

SDS number: RE1000035901

Recommended restrictions
Recommended use: Adhesive
Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information

Distributor

Company Name: ULTIMATE SUPPORT Address: 3581 LARCH LANE JACKSON, MO 63755

US

Telephone: 800-525-5628

Emergency telephone number: 1-866-836-8855

2. Hazard(s) identification

Hazard Classification Physical Hazards

Flammable aerosol Category 1

Health Hazards

Serious Eye Damage/Eye Irritation Category 2A
Skin sensitizer Category 1
Specific Target Organ Toxicity - Category 3
Single Exposure (Narcotic effect.)

Environmental Hazards

Acute hazards to the aquatic Category 3

environment

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Extremely flammable aerosol.

Causes serious eye irritation.

May cause an allergic skin reaction. May cause drowsiness or dizziness.

Harmful to aquatic life.

Revision Date: 04/16/2021

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well-ventilated area. Avoid release to the

environment.

Response: IF INHALED: Remove person to fresh air and keep comfortable for

breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of water If skin irritation or rash occurs: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. Specific treatment (see

on this label). Wash contaminated clothing before reuse.

Storage: Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F. Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC):

None

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
2-Propanone	67-64-1	20 - <50%
Propane	74-98-6	10 - <20%
Butane	106-97-8	10 - <20%
Acetic acid, methyl ester	79-20-9	5 - <10%
Naphtha (petroleum), hydrotreated light	64742-49-0	5 - <10%
Benzene, 1-chloro-4-(trifluoromethyl)-	98-56-6	1 - <5%
Methane, 1,1'-oxybis-	115-10-6	1 - 5%
Heptane	142-82-5	1 - <5%
Maleic Anhydride Modified Liquid Polyisoprene	841251-34-1	1 - <5%

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

The exact concentration has been withheld as a trade secret.

4. First-aid measures

Description of necessary first-aid measures

Inhalation: Move to fresh air.

Skin Contact: If skin irritation occurs: Get medical advice/attention. Destroy or

thoroughly clean contaminated shoes. Immediately remove

contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get

medical attention.

Revision Date: 04/16/2021

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy

to do, remove contact lenses. Get medical attention.

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Personal Protection for First-

aid Responders:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

Most important symptoms/effects, acute and delayed

Symptoms: No data available.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Fight fire from a

protected location. Move containers from fire area if you can do so without

risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

Vapors may travel considerable distance to a source of ignition and flash

back.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Accidental release measures: Prevent entry into waterways, sewer, basements or confined areas. Stop

the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you

can do so without risk.

Methods and material for containment and cleaning up:

Absorb spill with vermiculite or other inert material, then place in a container

for chemical waste.

Revision Date: 04/16/2021

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or

spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Handling

Technical measures (e.g. Local and general ventilation):

No data available.

Safe handling advice: Avoid contact with eyes. Wash hands thoroughly after handling. Keep away

from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use. Avoid contact

with eyes, skin, and clothing.

Contact avoidance measures: No data available.

Storage

Safe storage conditions: Pressurized container: protect from sunlight and do not expose to

temperatures exceeding 50°C. Do not pierce or burn, even after

use.Aerosol Level 2

Safe packaging materials: No data available.

Storage Temperature: No data available.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Туре	Exposure L	imit Values	Source
2-Propanone	STEL	1,000 ppm	2,400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	PEL	1,000 ppm	2,400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	250 ppm		US. ACGIH Threshold Limit Values, as amended
	TWA	750 ppm	1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	STEL	500 ppm		US. ACGIH Threshold Limit Values, as amended
	REL	250 ppm	590 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Propane	REL	1,000 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Butane	REL	800 ppm	1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	STEL	1,000 ppm		US. ACGIH Threshold Limit Values, as amended
	TWA	800 ppm	1,900 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Acetic acid, methyl ester	REL	200 ppm	610 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	STEL	250 ppm	760 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL	200 ppm	610 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	STEL	250 ppm		US. ACGIH Threshold Limit Values, as amended
	TWA	200 ppm	610 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	STEL	250 ppm	760 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	TWA	200 ppm		US. ACGIH Threshold Limit Values, as amended

Revision Date: 04/16/2021

		T		T
Naphtha (petroleum), hydrotreated light	REL	100 ppm	400 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	TWA	100 ppm	400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	PEL	100 ppm	400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Heptane	TWA	400 ppm	1,600 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	REL	85 ppm	350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	STEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	TWA	400 ppm		US. ACGIH Threshold Limit Values, as amended
	STEL	500 ppm		US. ACGIH Threshold Limit Values, as amended
	Ceil_ Time	440 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Cyclohexane, methyl-	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	400 ppm	1,600 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	TWA	400 ppm		US. ACGIH Threshold Limit Values, as amended
	REL	400 ppm	1,600 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Methanol	STEL	250 ppm	325 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	TWA	200 ppm		US. ACGIH Threshold Limit Values, as amended
	STEL	250 ppm		US. ACGIH Threshold Limit Values, as amended
	STEL	250 ppm	325 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	REL	200 ppm	260 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL	200 ppm	260 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	200 ppm	260 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Cyclohexane	TWA	100 ppm		US. ACGIH Threshold Limit Values, as amended
	TWA	300 ppm	1,050 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	REL	300 ppm	1,050 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL	300 ppm	1,050 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Hexane	TWA	50 ppm	180 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	PEL	500 ppm	1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	REL	50 ppm	180 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards,
	TWA	50 ppm		as amended US. ACGIH Threshold Limit Values, as amended
Talc (Mg3H2(SiO3)4) - Respirable fraction.	TWA	оо ррии	2 mg/m3	US. ACGIH Threshold Limit Values, as amended
Talc (Mg3H2(SiO3)4) - Respirable.	REL		2 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Talc (Mg3H2(SiO3)4) -	TWA		2 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as
Respirable dust. Talc (Mg3H2(SiO3)4)	TWA		20 millions of particles per cubic foot of air	amended US. OSHA Table Z-3 (29 CFR 1910.1000), as amended
Talc (Mg3H2(SiO3)4) -	TWA		2.4 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000), as
Respirable.	TWA		per cubic foot of air 0.1 mg/m3	amended US. OSHA Table Z-3 (29 CFR 1910.1000), as
Benzene, methyl-	STEL	150 ppm	560 mg/m3	amended US. OSHA Table Z-1-A (29 CFR 1910.1000), as
· •	REL	100 ppm	375 mg/m3	amended US. NIOSH: Pocket Guide to Chemical Hazards,
	TWA	100 ppm	375 mg/m3	as amended US. OSHA Table Z-1-A (29 CFR 1910.1000), as
			or o mg/mo	amended US. OSHA Table Z-1-A (29 CFR 1910.1000), as
	Ceiling	300 ppm		amended
	TWA	20 ppm 200 ppm		US. ACGIH Threshold Limit Values, as amended US. OSHA Table Z-2 (29 CFR 1910.1000), as
	MAX.	500 ppm		amended US. OSHA Table Z-2 (29 CFR 1910.1000), as
	CONC			amended

Revision Date: 04/16/2021

	STEL	150 ppm	560 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Benzene, ethyl-	STEL	125 ppm	545 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	STEL	125 ppm	545 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	TWA	100 ppm	435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	TWA	20 ppm		US. ACGIH Threshold Limit Values, as amended
Naphthalene	STEL	15 ppm	75 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	REL	10 ppm	50 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL	10 ppm	50 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	10 ppm	50 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	TWA	10 ppm		US. ACGIH Threshold Limit Values, as amended
	STEL	15 ppm	75 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Benzene	REL	0.1 ppm		US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	TWA	1 ppm		US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	Ceiling	25 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended
	TWA	0.5 ppm		US. ACGIH Threshold Limit Values, as amended
	STEL	2.5 ppm		US. ACGIH Threshold Limit Values, as amended
	STEL	5 ppm		US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended
	OSHA_ ACT	0.5 ppm		US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended
	TWA	10 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended
	MAX. CONC	50 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended
	STEL	5 ppm		US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	TWA	1 ppm		US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended
	STEL	1 ppm		US. NIOSH: Pocket Guide to Chemical Hazards, as amended

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
2-Propanone (acetone: Sampling time: End of shift.)	25 mg/l (Urine)	ACGIH BEL
Methanol (methanol: Sampling time: End of shift.)	15 mg/l (Urine)	ACGIH BEL
Hexane (2,5-Hexanedion, without hydrolysis: Sampling time: End of shift.)	0.5 mg/l (Urine)	ACGIH BEL
Benzene, methyl- (toluene: Sampling time: End of shift.)	0.03 mg/l (Urine)	ACGIH BEL
Benzene, methyl- (o-Cresol, with hydrolysis: Sampling time: End of shift.)	0.3 mg/g (Creatinine in urine)	ACGIH BEL
Benzene, methyl- (toluene: Sampling time: Prior to last shift of work week.)	0.02 mg/l (Blood)	ACGIH BEL
Benzene, ethyl- (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL
Benzene (S-Phenylmercapturic acid: Sampling time: End of shift.)	25 μg/g (Creatinine in urine)	ACGIH BEL
Benzene (t,t-Muconic acid: Sampling time: End of shift.)	500 μg/g (Creatinine in urine)	ACGIH BEL

Exposure guidelines

Methanol	US. ACGIH Threshold Limit Values, as amended	Can be absorbed through the skin.
Hexane	US. ACGIH Threshold Limit Values, as amended	Can be absorbed through the skin.
Naphthalene	US. ACGIH Threshold Limit Values, as amended	Can be absorbed through the skin.
Benzene	US. ACGIH Threshold Limit Values, as amended	Can be absorbed through the skin.

Appropriate Engineering Controls

No data available.

Individual protection measures, such as personal protective equipment

Eye/face protection: Wear safety glasses with side shields (or goggles).

Revision Date: 04/16/2021

Skin Protection

Hand Protection: No data available.

Skin and Body Protection: Wear suitable protective clothing. Wear chemical-resistant gloves,

footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific

information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Avoid contact with eyes. When

using do not smoke. Contaminated work clothing should not be allowed out

of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state: liquid

Form: Spray Aerosol
Color: No data available.
Odor: No data available.
Odor Threshold: No data available.
pH: No data available.
Freezing point: No data available.

Boiling Point: 67.05 °C **Flash Point:** -104.44 °C

Evaporation Rate:No data available.
Flammability (solid, gas):
No data available.

Explosive limit - upper (%): 11.4 %(V)
Explosive limit - lower (%): 2.2 %(V)

310 - 448 hPa (20 °C) Vapor pressure: Vapor density (air=1): No data available. Density: No data available. Relative density: No data available. Solubility in Water: No data available. Solubility (other): No data available. Partition coefficient (n-octanol/water): No data available. **Self Ignition Temperature:** No data available. **Decomposition Temperature:** No data available. Kinematic viscosity: 10 - 200 mm2/s (12 °C) Dynamic viscosity: 10 - 200 mPa.s (12 °C) **Explosive properties:** No data available. **Oxidizing properties:** No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

Conditions to avoid: Avoid heat or contamination.

Revision Date: 04/16/2021

Incompatible Materials: No data available.

Hazardous Decomposition

Products:

No data available.

11. Toxicological information

Information on likely routes of exposure

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 33,852.44 mg/kg

Dermal

Product: ATEmix: 339,868.02 mg/kg

Inhalation

Product: ATEmix: 424.56 mg/l Dusts, mists and fumes

Repeated dose toxicity

Product: No data available.

Components:

2-Propanone NOAEL (Rat(Male), Oral, 13 Weeks): 10,000 ppm(m) Oral Experimental

result, Key study

Propane NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation

Experimental result, Key study

LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation

Experimental result, Key study

Butane LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation

Experimental result, Key study

NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation

Experimental result, Key study

Acetic acid, methyl ester NOAEL (Rat(Female, Male), Inhalation, 28 d): 350 ppm(m) Inhalation

Experimental result, Key study

LOAEL (Rat(Female, Male), Inhalation, 28 d): 2,000 ppm(m) Inhalation

Experimental result, Key study

Revision Date: 04/16/2021

Naphtha (petroleum), hydrotreated light

NOAEL (Rat(Female, Male), Inhalation): 10,000 mg/m3 Inhalation

Experimental result, Key study

LOAEL (Rat(Female, Male), Oral, 13 Weeks): 1,250 mg/kg Oral Readacross based on grouping of substances (category approach), Key study

NOAEL (Rat(Female, Male), Dermal, 28 d): > 375 mg/kg Dermal

Experimental result, Supporting study

Benzene, 1-chloro-4-(trifluoromethyl)- NOAEL (Rat(Male), Inhalation): 5.5 mg/m3 Inhalation Experimental result,

Key study

Methane, 1,1'-oxybis- NOAEL (Rat(Female, Male), Inhalation, 2 yr): 2.5 %(m) Inhalation

Experimental result, Key study

Heptane NOAEL (Rat(Male), Inhalation): 12,470 mg/m3 Inhalation Experimental

result, Key study

Skin Corrosion/Irritation

Product: No data available.

Components:

2-Propanone in vivo (Rabbit): Not irritant Acetic acid, methyl in vivo (Rabbit): Not irritant

ester

Naphtha (petroleum), hydrotreated light Benzene, 1-chloro-4Assessment Non-Irritating In vitro (Human): not corrosive

estimated Irritating.

(trifluoromethyl)-

Heptane in vivo (Rabbit): Irritating

Serious Eye Damage/Eye Irritation

Product: No data available.

Components:

2-Propanone Irritating.

Rabbit, 24 hrs: Minimum grade of severe eye irritant

Acetic acid, methyl

ester

Rabbit: Irritating

Naphtha (petroleum),

hydrotreated light

Rabbit, 24 - 72 hrs: Not irritating

Heptane Rabbit, 24 - 72 hrs: Not irritating

Respiratory or Skin Sensitization

Product: No data available.

Components:

2-Propanone Skin sensitization:, in vivo (Guinea pig): Non sensitising Skin sensitization:, in vivo (Guinea pig): Non sensitising

hydrotreated light

Heptane Skin sensitization:, in vivo (Guinea pig): Non sensitising

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified

Revision Date: 04/16/2021

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure
Product:

No data available.

Components:

2-Propanone Inhalation - vapor: Narcotic effect. - Category 3 with narcotic effects.

Heptane Narcotic effect. - Category 3 with narcotic effects.

Specific Target Organ Toxicity - Repeated Exposure
Product:
No data available.

Target Organs

Specific Target Organ Toxicity - Single Exposure: Narcotic effect.

Aspiration Hazard

Product: No data available.

Components:

Naphtha (petroleum),

hydrotreated light

May be fatal if swallowed and enters airways.

Heptane May be fatal if swallowed and enters airways.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Components:

2-Propanone LC 50 (Oncorhynchus mykiss, 96 h): 5,540 mg/l Experimental result, Key

study

Propane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Butane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Acetic acid, methyl ester LC 50 (Fathead minnow (Pimephales promelas), 96 h): 295 - 348 mg/l

Mortality

LC 50 (Danio rerio, 48 h): 250 - 350 mg/l Experimental result, Key study

Naphtha (petroleum), hydrotreated light

LC 50 (96 h): 8.41 mg/l Experimental result, Key study

Methane, 1,1'-oxybis- LC 50 (Various, 96 h): 1,783.04 mg/l QSAR QSAR, Supporting study

Heptane LC 50 (Mozambique tilapia (Tilapia mossambica), 96 h): 375 mg/l Mortality

Revision Date: 04/16/2021

Aquatic Invertebrates

Product: No data available.

Components:

2-Propanone LC 50 (Daphnia pulex, 48 h): 8,800 mg/l Experimental result, Key study

Butane LC 50 (Daphnia sp., 48 h): 69.43 mg/l QSAR QSAR, Key study

Acetic acid, methyl ester EC 50 (Daphnia magna, 48 h): 1,026.7 mg/l Experimental result, Key study

Naphtha (petroleum), hydrotreated light

EC 50 (Daphnia magna, 48 h): 4.5 mg/l Experimental result, Key study

Heptane EC 50 (Daphnia magna, 48 h): 1.5 mg/l Experimental result, Key study

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Components:

Naphtha (petroleum), hydrotreated light

NOAEL (Daphnia magna): 2.6 mg/l Other, Key study

Heptane NOAEL (Oncorhynchus mykiss): 1.284 mg/l QSAR QSAR, Key study

Aquatic Invertebrates

Product: No data available.

Components:

2-Propanone LOAEL (Daphnia magna): 2,212 mg/l Experimental result, Key study

NOAEL (Daphnia magna): 2,212 mg/l Experimental result, Key study

Naphtha (petroleum),

hydrotreated light

EC 50 (Daphnia magna): 10 mg/l Experimental result, Key study

Heptane NOAEL (Daphnia magna): 0.17 mg/l Read-across based on grouping of

substances (category approach), Key study

EC 50 (Daphnia magna): 0.23 mg/l Read-across based on grouping of

substances (category approach), Key study

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Components:

2-Propanone 90.9 % (28 d) Detected in water. Experimental result, Key study

Propane 100 % (385.5 h) Detected in water. Experimental result, Key study

50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study

Butane 100 % (385.5 h) Detected in water. Experimental result, Key study

Acetic acid, methyl ester 70 % Detected in water. Experimental result, Key study

Naphtha (petroleum), hydrotreated light

90.35 % (28 d) Detected in water. Experimental result, Supporting study

Methane, 1,1'-oxybis- 5 % (28 d) Detected in water. Experimental result, Key study

Revision Date: 04/16/2021

Heptane 70 % Detected in water. Experimental result, Key study

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Components:

2-Propanone Haddock, adult, Bioconcentration Factor (BCF): 0.69 Aquatic sediment

Experimental result, Not specified

Naphtha (petroleum), Bioconcentration Factor (BCF): 10 - 2,500 Aquatic sediment Estimated by

hydrotreated light calculation, Key study

Heptane Bioconcentration Factor (BCF): 552 Aquatic sediment Estimated by

calculation, Key study

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Components:

Naphtha (petroleum), hydrotreated light

Log Kow: > 2.4 - < 5.7 23 °C Yes Experimental result, Key study

Mobility in soil: No data available.

Components:

2-Propanone No data available. Propane No data available. Butane No data available. Acetic acid, methyl ester No data available. Naphtha (petroleum), hydrotreated light No data available. Benzene, 1-chloro-4-(trifluoromethyl)-No data available. Methane, 1,1'-oxybis-No data available. Heptane No data available. Maleic Anhydride Modified Liquid No data available.

Polyisoprene

Other adverse effects: Harmful to aquatic organisms.

13. Disposal considerations

Disposal instructions: Discharge, treatment, or disposal may be subject to national, state, or local

laws.

Contaminated Packaging: No data available.

14. Transport information

DOT

UN Number: UN 1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es)

Class: 2.1 Label(s): -

EmS No.:

Packing Group: -

Special precautions for user: Not regulated.

Revision Date: 04/16/2021

IATA

UN Number: UN 1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es):

Class: 2.1
Label(s): Packing Group: -

Special precautions for user: Not regulated.

Other information

Passenger and cargo aircraft: Allowed. 203
Cargo aircraft only: Allowed. 203

IMDG

UN Number: UN 1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es)

Class: 2.1
Label(s): –
EmS No.:

Packing Group:

Special precautions for user: Not regulated.

15. Regulatory information

US Federal Regulations

Restrictions on use: Not known.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

<u>Chemical Identity</u> <u>OSHA hazard(s)</u>

Benzene Flammability

Cancer Aspiration Eye Blood Skin

respiratory tract irritation Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity

2-Propanone ACETONE

UNLISTED HAZARDOUS WASTES CHARACTERISTIC OF IGNITABILITY

RCRA HAZARDOUS WASTE NO. D001

Acetic acid, methyl ester

METHANOL

METHYL ALCOHOL

CYCLOHEXANE

BENZENE, HEXAHYDRO-

HEXANE

Hexane

BENZENE, METHYL-

ETHYLBENZENE

NAPHTHALENE

BENZENE

Revision Date: 04/16/2021

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Flammable aerosol, Serious Eye Damage/Eye Irritation, Skin sensitizer, Specific Target Organ Toxicity - Single Exposure

US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

US State Regulations

US. California Proposition 65

For more information go to www.P65Warnings.ca.gov.

US. New Jersey Worker and Community Right-to-Know Act Chemical Identity

2-Propanone

Propane

Butane

Acetic acid, methyl ester

Naphtha (petroleum), hydrotreated light

Methane, 1,1'-oxybis-

Benzene, 1-chloro-4-(trifluoromethyl)-

Heptane

US. Massachusetts RTK - Substance List

No ingredient regulated by MA Right-to-Know Law present.

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

2-Propanone

Propane

Butane

Acetic acid, methyl ester

Naphtha (petroleum), hydrotreated light

Methane, 1,1'-oxybis-

Heptane

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

International regulations

Montreal protocol

2-Propanone

Acetic acid, methyl ester

Stockholm convention

2-Propanone

Acetic acid, methyl ester

Rotterdam convention

2-Propanone

Acetic acid, methyl ester

Revision Date: 04/16/2021

Kyoto protocol

Inventory Status:

Australia AICS Not in compliance with the inventory.

Canada DSL Inventory List On or in compliance with the inventory

EINECS, ELINCS or NLP Not in compliance with the inventory.

Japan (ENCS) List Not in compliance with the inventory.

China Inv. Existing Chemical Substances

On or in compliance with the inventory

Korea Existing Chemicals Inv. (KECI)

Not in compliance with the inventory.

Canada NDSL Inventory Not in compliance with the inventory.

Philippines PICCS Not in compliance with the inventory.

US TSCA Inventory On or in compliance with the inventory

New Zealand Inventory of Chemicals Not in compliance with the inventory.

Japan ISHL Listing Not in compliance with the inventory.

Japan Pharmacopoeia Listing

Not in compliance with the inventory.

Mexico INSQ Not in compliance with the inventory.

Ontario Inventory Not in compliance with the inventory.

Taiwan Chemical Substance Inventory Not in compliance with the inventory.

16.Other information, including date of preparation or last revision

Issue Date: 04/16/2021

Revision Information: No data available.

Version #: 1.1

Further Information: No data available.

Disclaimer: This information is provided without warranty. The information is believed to

be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.