




## ROTATION RESISTANT **35 x 7**

The 35 x 7 rotational resistant wire rope has maximum resistance to rotation and is suitable for use on single part and multi-part hoist reeving systems.



- High fatigue life resulting from the unique compaction process
- Increased resistance to crushing. Recommended for multi-layer spooling operations
- Increased abrasion resistance resulting from the unique compaction process
- Optional plastic impregnation. (P) signifies full plastic impregnation of the Steel Core
- Fully lubricated in manufacturing
- Galvanised to add extra protection to the elements

WIRE ROPE DIA		APPROX MASS (kg/100m)	MIN BREAKING FORCE
mm	inches		ROPE GRADE 1960 N/mm <sup>2</sup> (kN)
	1/2	81.1	148
13		85.0	155
14		98.6	180
16		129	233
18		163	300
19		182	331
20		201	372
21		222	402
22		243	444
	7/8	249	453
24		290	531
	1	325	591
26		340	621
28		394	720
	1-1/8	411	748

WIRE ROPE DIA		APPROX MASS (kg/100m)	MIN BREAKING FORCE
mm	inches		ROPE GRADE 1960 N/mm <sup>2</sup> (kN)
30		453	827
32		515	944
35		616	1125
36		652	1185
38		726	1326
40		805	1477
42		887	1485
44		974	1618
	1-3/4	994	1646
46		1064	1765
48		1159	1935
50		1258	2078
	2	1298	2150
52		1360	2256

We're Australia's leading online supplier of lifting equipment and partner with some of the most trusted brands in the world to deliver quality products at competitive prices.