Technical Data Sheet





Aerosol can storage cage: 220 to 315 can capacity*

APPLICATION

For the safe and secure storage of aerosol cans.

FEATURES

- Heavy duty zinc anneal steel construction
- Durable UV-stabilised powder-coated yellow finish
- High open-area perforated side panels for natural ventilation in accordance with Australian Standards
- Solid steel roof and base
- Five fixed shelves (including base)
- Pre-drilled mounting feet (bolt down plates)
- Lockable door fitted with two magnetic latches and padlock lug (padlock not included)
- Manufactured in Australia to comply with Australian Standards
- Safety and warning signage in accordance with Australian Standards



SPECIFICATIONS	
Product name	Aerosol can storage cabinet
Code	SCAR220
Maximum storage capacity	315 aerosol cans (65mm ø x 245mm high)
Construction material	Zinc anneal steel
Surface finish	UV-stabilised polyester powder
Paint colour	Yellow
Doors	1
Shelves (including base)	5
Bolt down plates	4x pre-drilled holes - 8mm Ø
Shipping weight	57kg

MANUFACTURED TO MEET THE REQUIREMENTS OF		
AS/NZS3833-2007	The storage and handling of mixed classes of dangerous goods, in packages and intermediate bulk containers	
AS1319-1994	Safety signs for the occupational environment	
ADG CODE 7.5	Australian Dangerous Goods Code 2017 Edition 7.5	
AS4506-2005	Metal finishing - Thermoset powder coatings	

CAMERA SMOKING ROGATION SQUEES WITHIN SWETES	Ø	
PLANTEZ 2		
AEROSOLS ONLY		

DIMENSIONS (W x D x H)		
External dimensions	665mm x 465mm x 1720mm	
Internal dimensions	585mm x 400mm x 1700mm	



Class 2: Flammable Gas

Flammable gases are gases which at 20°C and a standard pressure of 101.3 kPa:
(i) are ignitable when in a mixture of 13 per cent or less by volume with air; or
(ii) have a flammable range with air of at least 12 percentage points regardless of the lower flammable limit. Flammability should be determined by tests or by calculation in accordance with methods adopted by ISO (see ISO 10156:2010).

Referenced from the Australian Dangerous Goods Code, 2017, Edition 7.5 $\,$