Technical Data Sheet





9kg LPG gas storage cage - 16x P cylinders

APPLICATION

For the safe and secure storage of 9kg BBQ LPG cylinders.

FEATURES

- · Heavy duty zinc anneal steel construction
- Two-coat protective finish for outdoor use
- High open-area perforated side panels for natural ventilation in accordance with Australian Standards
- Solid steel roof and base
- Two fixed shelves (including base)
- Lockable doors fitted with magnetic latch and padlock lug (padlock not included)
- Pre-drilled mounting feet (bold down plates)
- Manufactured in Australia to comply with the requirements of AS4332-2004
- Safety and warning signage in accordance with Australian Standards



SPECIFICATIONS	
Product name	9kg BBQ LPG gas storage cage
Code	SCGR16P
Maximum storage capacity	16x 9kg P cylinders
Construction material	Zinc anneal steel
Surface finish	Epoxy powder undercoat + UV-stabilised polyester powder topcoat
Paint colour	Deep ocean blue
Doors	2
Shelves (including base)	12
Bolt down plates	4x pre-drilled holes - 10mm Ø
Shipping weight	115kg

MANUFACTURED TO MEET THE REQUIREMENTS OF		
AS4332-2004	The storage and handling of gases in cylinders	
AS1319-1994	Safety signs for the occupational environment	
ADG CODE 7.5	Australian Dangerous Goods Code 2017 Edition 7.5	
AS4506-2005	Metal finishing - Thermoset powder coatings	

DIMENSIONS (W x D x H)		
External dimensions	1365mm x 755mm x 1190mm	
Internal dimensions	1260mm x 690mm x 1140mm	



Class 2: Flammable Gas

Flammable gases are gases which at 20°C and a standard pressure of 101.3 kPa:
(i) are ignitable when in a mixture of 13 per cent or less by volume with air; or
(ii) have a flammable range with air of at least 12 percentage points regardless of the lower flammable limit. Flammability should be determined by tests or by calculation in accordance with methods adopted by ISO (see ISO 10156:2010).

Referenced from the Australian Dangerous Goods Code, 2017, Edition 7.5 $\,$