Technical Data Sheet





Flammable liquids safety cabinet - 60L storage capacity

APPLICATION

For the safe and secure indoor storage of Class 3 flammable liquids and combustible liquids.

FEATURES

- Double wall construction with 40mm thermal barrier
- Vent ports with integral flash arrestors fitted on each side
- Single self-closing door with stainless steel, three point bullet self-latching system
- · Adjustable hydraulic door closure
- Flush mount handle and key lock
- Continuous piano hinge on door delivers smooth closure
- One adjustable shelf plus fixed base shelf
- Internal spill containment bund with suspended perforated floor
- Durable UV stabilised thermosetting polyester powder coat finish
- · Grounding connector enables earthing if required
- · Adjustable screw-in feet for optional elevation
- Safety and warning signage applied in accordance with Australian Standards.



| SPECIFICATIONS | |
|--------------------------|----------------------------------|
| Product name | Flammable liquids safety cabinet |
| Code | SCIRF60 |
| Maximum storage capacity | 60 litres |
| Construction material | Steel |
| Surface finish | UV-stabilised polyester powder |
| Paint colour | Yellow |
| Doors | 1 |
| Shelves (including base) | 2 |
| Shelf positions | 5 |
| Shipping weight | 65kg |

| MANUFACTURED TO MEET THE REQUIREMENTS OF | |
|--|---|
| AS1940-2017 | The storage and handling of flammable and combustible liquids |
| AS1319-1994 | Safety signs for the occupational environment |
| ADG CODE 7.5 | Australian Dangerous Goods Code 2017 Edition 7.5 |
| AS4506-2005 | Metal finishing - Thermoset powder coatings |

| DIMENSIONS (W x D x H) | |
|------------------------|------------------------|
| External dimensions | 595mm x 475mm x 1005mm |
| Internal dimensions | 500mm x 375mm x 754mm |
| Shelf dimensions | 487mm x 320mm x 30mm |



Class 3: Flammable Liquids

Flammable liquids are liquids, or mixtures of liquids, or liquids containing solids in solution or suspension (for example, paints, varnishes, lacquers, etc., but not including substances otherwise classified on account of their dangerous characteristics) which give off a flammable vapour at temperatures of not more than 60 °C, closed-cup test, or not more than 65.6 °C, open-cup test, normally referred to as the flash point.

Referenced from the Australian Dangerous Goods Code, 2017, Edition 7.5 $\,$