



PRT89ACS 1000 lbs [455 kg]





THE ORIGINAL & TRUSTED NAME IN VACUUM LIFTING EQUIPMENT

908 West Main - P.O. Box 368 Laurel, Montana 59044 U.S.A. 406.628.8231 (phone) 406.628.8354 (fax)


> 800.548.7341 www.WPG.com


Wood's Powr-Grip products are sold through authorized dealers.

POWER ROTATOR/ TILTER 1000



With fully powered 360° rotation and 90° tilt, this Powr-Grip® vacuum lifter offers maximum ease in the manipulation of heavy materials on the production line.





Shown with optional High-Duty Tilt, Vacuum Loss Warning Buzzer and DC Back-Up System.

Warning Buzzer and DC Back-Up System.	
Standard Pad Spread	29¼" x 59¼" [740 x 1502 mm]
Number / Size of Pads	8 / 9" [23 cm] diameter
Load Capacity (On smooth, nonporous surfaces. Please contact us for recommendations on other surfaces.)	1000 lbs [455 kg]
Unit Weight	600 lbs [273 kg]
Standard Operating Power	120 volts AC, 60 hertz, 16 amps
Apply	4 seconds (approximately)
Release	3 seconds (approximately)
Load Movement	Power rotation, 360° edgewise, with adjustable speed control Power tilt, 90° between upright and flat
Maximum Rotation Speed	Full turn 7 sec. (approximately)
Minimum Rotation Speed	Full turn 30 sec. (approximately)
Time for 90° Tilt	13 seconds (approximately)
Tilt Duty	41 tilts per hour
Standard Features	Green lift light Vacuum gauge Movable control pendant Vacuum reserve tank Vacuum line filter Spring-mounted pads Twist-lock electrical plug Blow-off for quick release
Available Options	Voltage adaptation (EO6VA) DC power system (PRT89DCS) (Specifications may not be as listed above. Please contact us for more information.) High-duty tilt with speed control (LB1ETO) 12-Volt/DC vacuum back-up system (EO1DCB) Interchangeable pad frames (CF1IFO) Removable pad arms (CF2EAO) Vacuum loss warning buzzer (EO3VLW) Individual pad shutoffs (CM1COWB) Telescoping pad arms (CF3TAO) Movable pad mounts (CM2SCM)
Design Standards (See www.WPG.com for more information.)	ASME B30.20 - 2006 (BTH-1 Design Category "B", Service Class "0")