

• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®

MOISTURE STOP FORTIFYING SEALER

*For Concrete Floors
with Moisture*

*Apply Prior to
Coating or Staining*

*Strengthens & Seals
Concrete*

1 Gallon (128 Fl. Oz./3.78L)
See warnings on back panel

#1 TRUSTED
BRAND FOR
PROTECTION



**CREATES A
MOISTURE
BARRIER**



• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®

MOISTURE STOP FORTIFYING SEALER

*For Concrete Floors
with Moisture*

*Apply Prior to
Coating or Staining*

*Strengthens & Seals
Concrete*

1 Gallon (128 Fl. Oz./3.78L)
See warnings on back panel



**CREATES A
MOISTURE
BARRIER**



INTERIOR · EXTERIOR

INTERIOR · EXTERIOR

• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®

RUST-OLEUM® MOISTURE STOP penetrates into concrete and reacts with the free calcium and water to form a gel in cracks, pores and capillaries to protect against the ingress of water and contaminants. This allows surfaces that were previously uncoatable, due to moisture, to be coated. Suitable for interior and exterior use.

WHERE TO USE: For use on bare concrete and masonry surfaces such as Garage Floors, Driveways, Sidewalks, Walkways, Stairs, Patios, Pool Decks, Basements, Retaining Walls and Cinder Block Walls. Can be used as a curing agent on newly poured concrete within 28 days.

TESTING CONCRETE FOR MOISTURE: Apply a 2"x2" sheet of plastic to the garage floor. Tape down the edges with duct tape and let set for 24 hours. If water droplets form on the inside of the plastic or concrete appears wet (darker in color), moisture is trapped in the floor and **RUST-OLEUM® MOISTURE STOP** should be used prior to coating.

SURFACE PREPARATION: Remove any oil or grease with **RUST-OLEUM® CLEANER & DEGREASER** (sold separately). Scrub spots thoroughly with a stiff bristle brush or broom. Rinse thoroughly with fresh water, preferably with a power washer. Repeat as necessary to completely clean and rinse. Allow to dry. If coating the floor use **RUST-OLEUM® CLEAN & ETCH** and follow with **RUST-OLEUM® MOISTURE STOP**.

COVERAGE: New Concrete: 200 Sq.Ft. per Gallon, Old Concrete: 150 Sq.Ft. per Gallon, areas with crazing (fine cracks on the surface) may take two applications.

APPLICATION: RUST-OLEUM® MOISTURE STOP is ready to use. Do not thin. Use only when air (ambient) temperature is 50-90°F (10-32°C) and relative humidity is below 85%.

1. Shake bottle vigorously for 30-45 seconds.
2. Completely saturate the surface at 150-200 Sq.Ft./Gal using a low-pressure sprayer or by pouring onto surface.
3. Move product around on the floor with a stiff bristle broom or squeegee to work the product onto the floor.
4. Using a hose or sprayer, mist the surface with water to keep the floor wet for 30-45 minutes.
5. After 45 minutes, squeegee or broom excess moisture from the surface.
6. **IMPORTANT!** Wait a minimum of 2 hours, then flush the surface with water and squeegee to a surface dry condition. Failure to flush the surface will result in the appearance of efflorescence and will require the use of a separate Efflorescence Remover.

DRY TIME: Surface is ready for foot traffic after 2 hours and auto traffic after 12 hours, after flushing the surface. Surface can be coated as soon as it is dry.

CLEAN UP: Wash tools and equipment with soap and warm water. Properly dispose of all soiled rags and protect unused product from freezing.

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-866-765-4474 for a product replacement or full refund of the purchase price. Refer to product number and batch code on bottom of box.

PRECAUTIONS. May cause eye, nose, throat and skin irritation. **Use only with adequate ventilation.** Close container after each use. Wash thoroughly after handling.

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

KEEP OUT OF REACH OF CHILDREN-DO NOT TAKE INTERNALLY

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-866-765-4474 for a product replacement or full refund of the purchase price. Refer to product number.

Waterproofing Concrete/Masonry Sealer
VOC < 100 g/L

301239 Moisture Stop

RUST-OLEUM
CORPORATION

11 Hawthorn Pkwy., Vernon Hills, IL 60061
800-481-4785 | rustoleum.com

Made in USA

©2017 Rust-Oleum Corporation 327708 0517 0

