• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®

• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®

CLEAN & ETCHFOR CONCRETE

For Maximum Adhesion of Coatings, Paints & Stains

Properly Prepares Concrete Surfaces

Safe Near Plants & Grass

1 Gallon (128 Fl. Oz./3.78L)

DANGER! CAUSES BURNS TO EYES, SKIN & RESPIRATORY IRRITANT.
See other warnings on back panel.

TRUSTED BRAND FOR PROTECTION

CLEAN & ETCH FOR CONCRETE

For Maximum Adhesion of Coatings, Paints & Stains

Properly Prepares Concrete Surfaces

Safe Near Plants & Grass

1 Gallon (128 Fl. Oz./3.78L)

DANGER! CAUSES BURNS TO EYES, SKIN & RESPIRATORY IRRITANT.
See other warnings on back panel.

·INTERIOR · EXTERIOR ·

-INTERIOR - EXTERIOR |

• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®

RUST-OLEUM® CLEAN & ETCH is an etching solution used to clean and degrease bare concrete surfaces to improve penetration and adhesion of coatings, paints, stains and sealants. It also neutralizes the pH of new concrete. Suitable for interior and exterior use, RUST-OLEUM® CLEAN & ETCH is safe to use near grass and plants.

WHERE TO USE: Ideal for use on bare concrete: garage floors, basements, driveways, carports, patios, walkways and pool decks.

IMPORTANT: Read all instructions thoroughly. Wear safety goggles with side shields, rubber gloves and protective footwear.

SURFACE PREPARATION: Newly poured concrete must cure for a minimum of 30 days prior to cleaning or coating. Sweep surface to remove dirt and dust. Use RUST-OLEUM® CLEANER & DEGREASER to remove oily stains prior to using Clean & Etch.

COVERAGE: 500 Sq. Ft.

MIXING: Slowly add 1-gallon (full container) of the RUST-OLEUM® CLEAN & ETCH to a gallon of water in a plastic watering can (2 gallons total).

APPLICATION:

- Working in a 10ft x 10ft section of the floor, pour the mixed etching solution out evenly over the surface.
- Scrub the solution around with a stiff bristle broom. The etching solution may fizz for a few seconds while being scrubbed.
- When the fizzing stops, rinse off solution with clean water and moveto the next section. Product should not be allowed to dry on the surface. Mist the surface as necessary to keep wet until ready to rinse
- 4. When all sections are completed, rinse 3 times with clean water and scrubwith a stiff bristle brush while rinsing. This will ensure no product remains on the surface. The surface should feel rough, like 150 grit sandpaper and water should easily be absorbed into the concrete.
- Allow the surface to dry completely before applying any coatings, paints, stains or sealers. A squeegee will aid in the removal of excess water.

LIMITATIONS: Do not apply to concrete that has already been sealed, painted or stained as it will not etch the concrete.

CLEAN UP & STORAGE: Clean all application tools with water immediately after use. Keep product from freezing-do not store at temperatures helpus 50°C.

DANGER: CAUSES BURNS TO EYES. SKIN & RESPIRATORY IRRITANT. MAY BE HARMFUL IF SWALLOWED.

Contains Urea Monohydrochloride.

Avoid contact with eyes, skin and mucous membranes. Use only with adequate ventilation. Do not breathe vapors. Do not take internally. Wear chemical-resistant gloves and safety goggles with side shields when using this product. Wash contaminated clothing before reuse.

FIRST AID: In case of eye contact, flush with water for 15 minutes and get immediate medical attention. In case of skin contact, wash thoroughly with soap and water. If irritation persists, get medical attention. If swallowed, do not induce vomiting. Drink 2-3 glasses of water and get immediate medical attention. If vapors are inhaled or breathing becomes difficult, move person to fresh air. If symptoms persist, get medical attention.

KEEP OUT OF REACH OF CHILDREN AND ANIMALS

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-866-765-4474 for a product replacement or full refund of the purchase price. Refer to product number and batch code on bottom of box.

RUST-OLEUM

11 Hawthorn Pkwy., Vernon Hills, IL 60061 800-481-4785 | rustoleum.com

Made in USA | Hecho en E.U.A. ©2017 Rust-Oleum Corporation 327755 0517 20066|32253

301242 CLEAN & ETCH

5