

• TRUSTED QUALITY SINCE 1921 •

# RUST-OLEUM®

## ***PAIN*T STRIPPER FOR CONCRETE**

*For Previously Coated  
Concrete Floors*

*Removes Layers of  
Paint, Sealers & Epoxies*

*Gel Formula  
Spreads Evenly*

1 Gallon (128 Fl. Oz./3.78L)

**WARNING!** EYE AND SKIN IRRITANT  
See other cautions on back panel

342091

**#1 TRUSTED  
BRAND FOR  
PROTECTION**



• TRUSTED QUALITY SINCE 1921 •

# RUST-OLEUM®

## ***PAIN*T STRIPPER FOR CONCRETE**

*For Previously Coated  
Concrete Floors*

*Removes Layers of  
Paint, Sealers & Epoxies*

*Gel Formula  
Spreads Evenly*

1 Gallon (128 Fl. Oz./3.78L)

**WARNING!** EYE AND SKIN IRRITANT  
See other cautions on back panel



***INTERIOR · EXTERIOR***

***INTERIOR · EXTERIOR***

• TRUSTED QUALITY SINCE 1921 •

# RUST-OLEUM®

**RUST-OLEUM® PAINT STRIPPER** is designed to remove paint, stains and film forming sealers from garage floors and other concrete surfaces prior to applying a new coating. It is formulated to stay in place so it removes multiple layers of paint at one time, requiring only one application. The thicker consistency also allows it to be used on vertical surfaces.

**IMPORTANT:** Read all instructions thoroughly. Wear safety goggles with side shields, rubber gloves and protective footwear.

**WHERE TO USE:** Ideal for use on painted, stained or sealed interior and exterior surfaces such as concrete, masonry, stone and brick.

**LIMITATIONS:** Prior to use, test a small area of the floor to ensure the product will lift the coating. Some 2-part epoxy products will require a second application or will need to be sanded or ground.

**SURFACE PREPARATION:** Cover any plants or grass that could come in contact with the product or removed coating with plastic drop cloths. For vertical surfaces, scuff sand with medium grit sandpaper prior to application to assist with the Paint Stripper clinging to the surface.

**COVERAGE:** Up to 75 Sq. Ft. per gallon

#### APPLICATION:

1. Shake well before use.
2. Pour **RUST-OLEUM® PAINT STRIPPER** directly onto floor at full strength (do not dilute) in a thick layer. If applying to a vertical surface, scuff sand the surface prior to application to assist with the product clinging.
3. Lightly move product around on the floor with a stiff bristle brush to ensure even coverage. Don't scrub. Apply more product to areas that appear thin.
4. **RUST-OLEUM® PAINT STRIPPER** must remain on the surface and be allowed to penetrate for all of the layers of paint or stain to be removed. Re-apply product as necessary to keep the entire surface covered with a thick layer of Paint Stripper.
5. Once the coating is visually wrinkled it is ready to be removed. Test an area to see if it removes easily with a scraper. If it does not remove easily, apply additional product to the surface. This removal may take 30 minutes to 5 hours, depending on the type of coating being removed. Floors with multiple layers or more aggressive coatings will require the longest time.
6. Remove the coating using a scraper or stiff bristle brush.
7. Thoroughly rinse surface three times to ensure all of the Paint Stripper has been removed as it could prevent adhesion when recoating.

**DRY TIME:** Allow floor to dry for at least 24 hours before staining, sealing or coating.

**CLEAN UP:** Wash tools and equipment with soap and warm water. Properly dispose of all soiled rags and coating that has been removed.

**WARNING!** Contains Benzyl Alcohol and Formic Acid. Harmful if swallowed. Avoid breathing vapors. Use only with adequate ventilation. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, increase fresh air. Close container after each use. Avoid contact with eyes, skin and clothing. Wash hands thoroughly after handling.

KEEP OUT OF REACH OF CHILDREN.

#### FIRST AID:

**Eye Contact:** Flush eyes with plenty of water for at least 15 minutes. Get medical attention.  
**Skin Contact:** Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists. Get medical attention.

**Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. Get medical attention. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

**Ingestion:** If swallowed, do not induce vomiting. Call a physician or poison control center immediately.

⚠ **WARNING:** Cancer – www.P65Warnings.ca.gov.

**SATISFACTION GUARANTEED:** If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-866-765-4474 for a product replacement or full refund of the purchase price. Refer to product number and batch code on bottom of box.

**RUST-OLEUM**

**CORPORATION**

11 Hawthorn Pkwy., Vernon Hills, IL 60061

800-481-4785 | rustoleum.com

Made in USA

©2018 Rust-Oleum Corporation 342090 0418 0 20066 34402 3

310984 Paint Stripper



342090 310984 RO PAINT STRIPPER BK.indd 1

CYAN MAG YEL BLACK

5/7/18 1:05 PM



Flexible Packaging & Label Specialists  
 22790 Heslip  
 Novi, Michigan 48375  
 800/748-0203 • 248/335-7440  
 www.anchorprinting.com

#### Specs:

Size: 1 Gallon Plastic

Stock: Avery AT20N 60#

5.875" x 5.125"

Coating: Lamination

071912

Please read the proof and specifications carefully. Any errors that are not acknowledged by the customer are NOT the responsibility of Anchor Printing. Customer approval is required for print production.



APPROVED  
OK TO PROCEED



NOT APPROVED  
SEND NEW PROOF

CUSTOMER INITIALS \_\_\_\_\_

#### Ink Colors



CYAN



MAGENTA



YELLOW



BLACK