


Scarify / Level / Smooth / Prep / Remove

SMITH FS200™

Compact Scarifier/Grinder

Portable Compact Scarifier/Grinder




Order Number	Power
FS200.H5	5.5HP Honda
Removal Cut Width	≤ 8" pp (20cm)
Weight	125 lbs (56.6 kg) w/o drum
Dimensions	42" L x 14" W x 39" H (106 cm x 36 cm x 99 cm)
Optional	• Cutter drum assemblies • Electric power • Edger

FS200™ Series Performance Benefits:

The SMITH FS200 compact scarifier/grinder repairs, improves and maintains asphalt and concrete surfaces with the right surface profile finishes.

- 20-year performance history
 - All-steel frame
 - Honda engine with throttle and safety stop
 - Front outboard feathering caster wheel
 - Fixed inboard wheel for straight line removal
 - Micro-depth-of-cut control settings
 - Height-adjustable vibration tension comfort grips
 - Vacuum port for dust-free operation
 - Dual maintenance-free bearings
 - Fast and easy side-loading cutter drum
 - Triple-drive belts with safety belt guard
- Options:**
- Variety of cutter drum assemblies
 - "Get-close-to-curb" edger assembly
 - Gas engine or electric motor
 - MaxiVac vacuum systems
 - Hour/tach maintenance meter

SMITHmfg.com





Deluxe compact multi-use combination scarifier/grinder (up to 8" removal width) powered by 5.5 HP Honda gasoline engine, fully assembled – just add oil, gas and select cutter drum. Includes the following standard and upgraded purchased accessories.

Weight: 125 lbs, (no cutter drum)

Dimensions: 14" x 43" x 38"

Construction: All-steel unitized heavy-duty construction, with industrial safety-yellow with black belt guard and grade-8 fasteners

Power: 5.5 HP Honda gasoline engine, easy-start with oil alert, manual shutoff and exclusive emergency engine stop with corded safety stop lanyard and speed control throttle cable at handle

Cut controls: Dual depth control settings, (1) quick-set lever to engage and disengage cutter drum, and (2) hand wheel for fine adjustments

Drive System: Maintenance-free dual sealed bearing hex drive system (no grease required) and industrial grade tri-V belt-drive pulley with safety guard

Dust and Debris Control: Chip shrouded brush guard for dust and debris control with vacuum dust-collection port and cap

Drive wheels: Balanced all-steel rear wheel carrier for depth control, with twin 5" OD x 2" W wheels. Front single feathering caster wheel (for smoothing scarified surfaces) and front fixed wheel (for removing straight lines)

Operator Push Handles: Height adjustable with vibration tension setting handlebar and heavy-duty comfort ergonomic grips. Lifting rings and tie downs for easy transport

Quick Cutter-Drum Access: Removable side plate for side-loading drum with no exposed parts

Choice of Cutter Tool Drums: To Flail-it, Strip-it, Mill-it, Scrape-it, or Finish-it in fine, medium, coarse off-set, or inline removal patterns

OPTIONAL ease-of-operation and maintenance accessories to purchase separately include:

- a) Choice of cutter tool drum assemblies to Flail-it, Strip-it, Mill-it, Prep-it Scrape-it, and Finish-it in fine, medium, coarse off-set or inline removal patterns
- b) Edger assembly (PN: FS200.EDG.ACC) with Flail-it cutter drum assembly (PN: 504.4124.10), with choice of Flail-it, Strip-it, Mill-it, Scrape-it, or Finish-it in fine, medium, coarse off-set, or inline removal patterns
- c) HEPA MaxiVac gasoline or electric-powered dust collector
- d) Tach/hour meter (PN: 1068055)
- e) Water control system
- f) Power options: Electric 1.5HP 110v, 2HP 110v, 2HP 220v, 3HP 220v
- h) Extended warranty package with purchase of wear parts kit