Tenax Spa Revision nr.4 Dated 10/3/2019 Printed on 11/6/2020 Page n. 1 / 10 Replaced revision:3 (Dated 12/17/2018) **FIXTOP DECK B** Safety Data Sheet According to U.S.A. Federal Hazcom 2012 1. Identification 1.1. Product identifier **FIXTOP DECK B** Product name 1.2. Relevant identified uses of the substance or mixture and uses advised against Intended use epoxy mastic **Identified Uses** Industrial Professional Consumer ADHESIVE SYSTEM/TREATMENT FOR STONE SECTOR 1.3. Details of the supplier of the safety data sheet Name **Tenax Spa** Full address Via I Maggio, 226 (VR) District and Country 37020 Volargne Italy +39 045 6887593 Tel. +39 045 6862456 Fax e-mail address of the competent person responsible for the Safety Data Sheet msds@tenax.it Product distribution by: **Tenax Usa** 7606 Whitehall Executive Center Drive Suite 400, 28273 Charlotte NC, US Tel. 001 7045831173 - Fax 001 7045833166 info@tenaxusa.com 1.4. Emergency telephone number For urgent inquiries refer to Infotrac US and Canada: 1-800-535-5053 Int'l: 1-352-323-3500 info@infotrac.net 2. Hazards identification 2.1. Classification of the substance or mixture The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR

1910.1200). The product thus requires a safety datasheet. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement Skin corrosion, category 1 Serious eye damage, category 1 Skin sensitization, category 1

Hazard pictograms:



Signal words:

Danger

Hazard statements: H314 H317

Causes severe skin burns and eye damage. May cause an allergic skin reaction.

Causes severe skin burns and eye damage. Causes serious eye damage. May cause an allergic skin reaction.

Revision nr.4 Dated 10/3/2019 Printed on 11/6/2020 Page n. 2 / 10 Replaced revision:3 (Dated 12/17/2018)

2. Hazards identification

| Precautionary statement | IS: |
|-------------------------|--|
| Prevention: | |
| P260 | Do not breathe dust / fume / gas / mist / vapours / spray. |
| P280 | Wear protective gloves/ protective clothing / eye protection / face protection. |
| P264 | Wash the hands thoroughly after handling. |
| P272 | Contaminated work clothing should not be allowed out of the workplace. |
| Response: | |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. |
| | Continue rinsing. |
| P301+P330+P331 | IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower. |
| P310 | Immediately call a POISON CENTER / doctor / |
| P304+P340 | IF INHALED: remove person to fresh air and keep comfortable for breathing. |
| P302+P352 | IF ON SKIN: wash with plenty of water / |
| P363 | Wash contaminated clothing before reuse. |
| Storage: | |
| P405 | Store locked up. |
| Disposal: | |
| P501 | Dispose of contents / container according to applicable law. |
| | |

2.2. Other hazards

Information not available

3. Composition/information on ingredients

3.2. Mixtures

| Contains: | | | |
|---|---------------|----------------|---|
| Identification | Co | onc. % | Classification: |
| 3-AMINOME | THYL 3,5,5-TR | IMETHYLCYCLOHE | (YLAMINE |
| CAS | 2855-13-2 | 14 | Acute toxicity, category 4 H302, Acute toxicity, category 4 H312, Skin corrosion, category 1B H314, Serious eye damage, category 1 H318, Skin sensitization, category 1 H317, Hazardous to the aquatic environment, chronic toxicity, category 3 H412 |
| EC | 220-666-8 | | |
| INDEX | 612-067-00- | 9 | |
| BENZYL ALCOHOL | | | |
| CAS | 100-51-6 | 6 | Acute toxicity, category 4 H302, Acute toxicity, category 4 H332 |
| EC | 202-859-9 | | |
| INDEX | 603-057-00- | -5 | |
| AMINOETHYL AMINOPROPYL TRIMETHOXYSILANE | | | |
| CAS | 1760-24-3 | 0.99 | Acute toxicity, category 4 H302, Acute toxicity, category 4 H332, Serious eye damage, category 1 H318, Skin irritation, category 2 H315, Skin sensitization, category 1 H317 |
| EC INDEX | 217-164-6 | | |

The full wording of hazard (H) phrases is given in section 16 of the sheet.

4. First-aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Revision nr.4 Dated 10/3/2019 Printed on 11/6/2020 Page n. 3 / 10 Replaced revision:3 (Dated 12/17/2018)

Information not available

5. Fire-fighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations. SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with

self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

Revision nr.4 Dated 10/3/2019 Printed on 11/6/2020 Page n. 4 / 10 Replaced revision:3 (Dated 12/17/2018)

8. Exposure controls/personal protection

8.1. Control parameters

Information not available

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations. HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing. EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Properties | Value | Information |
|--|--------------------|-------------|
| Appearance | paste | |
| Colour | neutral | |
| Odour | characteristic | |
| Odour threshold | Not available | |
| pН | Not available | |
| Melting point / freezing point | Not available | |
| Initial boiling point | Not available | |
| Boiling range | Not available | |
| Flash point | > 93 °C | (199,4 °F) |
| Evaporation Rate | Not available | |
| Flammability of solids and gases | Not available | |
| Lower inflammability limit | Not available | |
| Upper inflammability limit | Not available | |
| Lower explosive limit | Not available | |
| Upper explosive limit | Not available | |
| Vapour pressure | Not available | |
| Vapour density | Not available | |
| Relative density | 1.37 g/cc | |
| Solubility | insoluble in water | |
| Partition coefficient: n-octanol/water | Not available | |
| Auto-ignition temperature | Not available | |
| Decomposition temperature | Not available | |
| Viscosity | Not available | |
| Explosive properties | Not available | |
| Oxidising properties | Not available | |
| .2. Other information | | |
| VOC : | 23,80 % - 326,06 | a/litre |

Revision nr.4 Dated 10/3/2019 Printed on 11/6/2020 Page n. 5 / 10 Replaced revision:3 (Dated 12/17/2018)

10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

BENZYL ALCOHOL

Decomposes at temperatures above 870°C/1598°F.Possibility of explosion.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

3-AMINOMETHYL 3,5,5-TRIMETHYLCYCLOHEXYLAMINE

May react dangerously with: strong oxidising agents, concentrated inorganic acids.

BENZYL ALCOHOL

May react dangerously with: hydrobromic acid, iron, oxidising agents, sulphuric acid. Risk of explosion on contact with: phosphorus trichloride.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

3-AMINOMETHYL 3,5,5-TRIMETHYLCYCLOHEXYLAMINE Avoid contact with: strong acids,strong oxidants.

BENZYL ALCOHOL

Avoid exposure to: air, sources of heat, naked flames.

10.5. Incompatible materials

BENZYL ALCOHOL

Incompatible with: sulphuric acid,oxidising substances,aluminium. 10.6. Hazardous decomposition products

Information not available

11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

BENZYL ALCOHOL LD50 (Oral) LD50 (Dermal) LC50 (Inhalation)

1230 mg/kg Rat 2000 mg/kg Rabbit > 4.1 mg/l/4h Rat

Revision nr.4 Dated 10/3/2019 Printed on 11/6/2020 Page n. 6 / 10 Replaced revision:3 (Dated 12/17/2018)

11. Toxicological information ...

SKIN CORROSION / IRRITATION

Corrosive for the skin

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

12. Ecological information

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

12.1. Toxicity

Information not available

12.2. Persistence and degradability

BENZYL ALCOHOL Rapidly degradable

3-AMINOMETHYL 3,5,5-TRIMETHYLCYCLOHEXYLAMINE

Solubility in water NOT rapidly degradable 1000 - 10000 mg/l

1.1

12.3. Bioaccumulative potential

BENZYL ALCOHOL

Partition coefficient: n-octanol/water

12.4. Mobility in soil

@EPY 9.11.0 - SDS 1004.13

Revision nr.4 Dated 10/3/2019 Printed on 11/6/2020 Page n. 7 / 10 Replaced revision:3 (Dated 12/17/2018)

12. Ecological information/

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Other adverse effects

Information not available

13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14. Transport information

14.1. UN number

ADR / RID, IMDG, IATA: 2289

14.2. UN proper shipping name

| ADR / RID: | ISOPHORONEDIAMINE SOLUTION |
|------------|----------------------------|
| IMDG: | ISOPHORONEDIAMINE SOLUTION |
| IATA: | ISOPHORONEDIAMINE SOLUTION |

14.3. Transport hazard class(es)

| ADR / RID: | Class: 8 | Label: 8 |
|------------|----------|----------|
| IMDG: | Class: 8 | Label: 8 |
| IATA: | Class: 8 | Label: 8 |



14.4. Packing group

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

| ADR / RID: | NO |
|------------|----|
| IMDG: | NO |
| IATA: | NO |

14.6. Special precautions for user

| ADR / RID: | HIN - Kemler: 80 | Limited Quantities: 5 L | Tunnel restriction code: (E) |
|------------|-----------------------|-------------------------|------------------------------|
| | Special Provision: - | | |
| IMDG: | EMS: F-A, S-B | Limited Quantities: 5 L | |
| IATA: | Cargo: | Maximum quantity: 60 L | Packaging instructions: 856 |
| | Pass.: | Maximum quantity: 5 L | Packaging instructions: 852 |
| | Special Instructions: | A803 | 0.0 |

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

Revision nr.4 Dated 10/3/2019 Printed on 11/6/2020 Page n. 8 / 10 Replaced revision:3 (Dated 12/17/2018)

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal Regulations

TSCA: All components are listed on TSCA Inventory.

Clean Air Act Section 112(b): 25322-68-3 POLYETHYLENGLYCOL (Glycol ethers)

Clean Air Act Section 602 Class I Substances: No component(s) listed.

Clean Air Act Section 602 Class II Substances: No component(s) listed.

Clean Water Act – Priority Pollutants: No component(s) listed.

Clean Water Act – Toxic Pollutants: No component(s) listed.

DEA List I Chemicals (Precursor Chemicals): No component(s) listed.

DEA List II Chemicals (Essential Chemicals): No component(s) listed.

EPA List of Lists: 313 Category Code: 25322-68-3 POLYETHYLENGLYCOL (Glycol ethers)

EPCRA 302 EHS TPQ: No component(s) listed.

EPCRA 304 EHS RQ: No component(s) listed.

CERCLA RQ: No component(s) listed.

EPCRA 313 TRI: 25322-68-3 POLYETHYLENGLYCOL (Glycol ethers)

RCRA Code: No component(s) listed.

CAA 112 (r) RMP TQ: No component(s) listed.

State Regulations

Massachussetts:

100-51-6 BENZYL ALCOHOL

Minnesota:

| 100-51-6 | BENZYL ALCOHOL |
|------------|-----------------------------------|
| 25322-68-3 | POLYETHYLENGLYCOL (Glycol ethers) |

New Jersey:

 2855-13-2
 3-AMINOMETHYL 3,5,5-TRIMETHYLCYCLOHEXYLAMINE

 25322-68-3
 POLYETHYLENGLYCOL (Glycol ethers)

 25322-68-3
 POLYETHYLENGLYCOL (Glycol ethers)

Revision nr.4 Dated 10/3/2019 Printed on 11/6/2020 Page n. 9 / 10 Replaced revision:3 (Dated 12/17/2018)

15. Regulatory information/>

New York: No component(s) listed.

Pennsylvania: 100-51-6 BENZYL ALCOHOL

California: No component(s) listed.

Proposition 65:

This product does not contain any substances know to the State of California to cause cancer, reproductive harm or birth defects.

International Regulations

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012: None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention: None

Candadian WHMIS Information not available

16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

| H302 | Harmful if swallowed. |
|------|--|
| H312 | Harmful in contact with skin. |
| H332 | Harmful if inhaled. |
| H314 | Causes severe skin burns and eye damage. |
| H318 | Causes serious eye damage. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H412 | Harmful to aquatic life with long lasting effects. |

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit

Revision nr.4 Dated 10/3/2019 Printed on 11/6/2020 Page n. 10 / 10 Replaced revision:3 (Dated 12/17/2018)

16. Other information

- VOC: Volatile organic Compounds- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh Registry of Toxic Effects of Chemical Substances
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Comunication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachussetts 105 CMR Department of public health 670.000: "Right to Know"
- Minensota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Product classification derives from criteria established by the OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200), unless determined otherwise in Section 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review: The following sections were modified: 02 / 03 / 09 / 11 / 12 / 14 / 15 / 16.