•TRUSTED QUALITY SINCE 1921•
RUST-OLEUM

RUST-OLEUM® PAINT STRIPPER

DESCRIPTION AND USES

Rust-Oleum® Paint Stripper is designed to easily remove paint, stains and film forming sealers from garage floors and other concrete surfaces prior to applying a new coating. It is formulated to remain on the applied surface so it removes multiple layers of paint at one time, requiring only one application. The thick consistency also allows it to be used on vertical surfaces.

It is suitable for use on painted, stained or sealed interior and exterior surfaces such as concrete, masonry, stone and brick.

PRODUCT FEATURES

- · Removes layers of paints, stains and sealers
- For use on concrete, masonry, stone and brick
- Gel formula spreads evenly & stays on surface until ready for removal
- For interior and exterior use

PRODUCT

SKU	DESCRIPTION
310984	1 Gallon Paint Stripper

PRODUCT APPLICATION

READ ALL INSTRUCTIONS CAREFULLY BEFORE STARTING PROJECT.

SURFACE PREPARATION

Cover any plants or grass that could come in contact with the product. For vertical surfaces, scuff sand with medium grit sandpaper prior to the application to help the Paint Stripper cling to the surface.

PRODUCT APPLICATION (cont.)

APPLICATION

Shake before use. Pour Rust-Oleum Paint Stripper directly onto the floor at full strength in a thick layer. **DO NOT DILUTE.** If applying to a vertical surface, scuff sand the surface prior to the application to help the product cling to the surface.

Lightly move the stripper around on the floor with a stiff bristle brush to ensure even coverage. Do not scrub. Apply more product to areas that appear thin.

Rust-Oleum Paint Stripper must remain on the surface and be allowed to penetrate all of the layers of paint or stain to be removed. Re-apply the product as necessary to keep the entire surface covered with a thick layer of Paint Stripper.

Once the coating is visually wrinkled, it is ready to be removed. Test an area to see if it removes easily with a scraper. If it does not remove easily, apply additional product to the surface. It may take 30 minutes to 5 hours for the coating to detach from the surface depending on the type of coating being removed. Floors with multiple layers or more aggressive coatings will require the longest time.

Remove the coating using a scraper or stiff bristle broom brush. Rinse the surface three times to ensure all of the Paint Stripper has been removed. Any remaining Paint Stripper could prevent adhesion when recoating.

COVERAGE

One gallon of Paint Stripper will cover up to 75 square feet. Results may vary based on substrate texture and porosity.

DRY TIME

Allow the floor to dry for at least 24 hours (after rinsing) before applying coating, staining or sealing.

CLEAN-UP

Wash tools and equipment with soap and warm water. Properly dispose of all soiled rags and coating that has been removed.

KEEP OUT OF REACH OF CHILDREN

Form: GDH-1358 Rev.: 072621 •TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM

RUST-OLEUM® PAINT STRIPPER

PHYSICAL PROPERTIES

		PAINT STRIPPER
Composition		Benzyl Alcohol, Formic Acid, Water
Weight	Per Gallon	8.5 lbs.
	Per Liter	1.02 kg
Solids	By Weight	<5%
	By Volume	<5%
Volatile Organic Compounds		<840 g/l
Coverage		One gallon of Paint Stripper will cover up to 75 square feet. Results may vary based on substrate texture and porosity.
Shelf Life		5 years
Flash Point		200°F (93°C)
Safety Inform	mation	For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Phone: 800·373·6333 www.rustoleum.com

Form: GDH-1358 Rev.: 072621