

Rivet Busters



Sold as shown



Sold as shown

Features

- ◆ Positive retention of piston
- ◆ Steel throttle valve
- ◆ Barrel has built-in bridge for safety
- ◆ Adjustable exhaust deflector
- ◆ Operates at 90 psi
- ◆ Inside or outside trigger for safety and control
- ◆ Heat treated polished steel barrel

Applications

- ◆ Road & bridge repair work
- ◆ Concrete demolition
- ◆ Rivet cutting up to $\frac{15}{16}$ " diameter
- ◆ Cement dressing
- ◆ Metal tank demolition
- ◆ Railroad car repair
- ◆ Concrete truck mixing tank cleaning

TOOL SPECIFICATIONS

MODEL #	WEIGHT	LENGTH	CFM CONSUMED	BORE	STROKE	SHANK	BPM	MINIMUM HOSE SIZE
TX-133-6RB	28.9 lbs.	20.75"	44 CFM	1-3/16"	6"	Jumbo .866"	1100	1/2"
TX-133-6RB-OT	13.1 kg	52.7 cm	75 m3/hr	30.2 mm	15.2 cm	Jumbo .866"		13 mm
TX-133-8RB	30.7 lbs.	22.75"	44 CFM	1-3/16"	8"	Jumbo .866"	960	1/2"
TX-133-8RB-OT	13.9 kg	57.8 cm	75 m3/hr	30.2 mm	20.3 cm	Jumbo .866"		13 mm
TX-133-11RB	33.5 lbs.	25.75"	50 CFM	1-3/16"	11"	Jumbo .866"	850	1/2"
TX-133-11RB-OT	15.2 kg	73.0 cm	85 m3/hr	30.2 mm	27.9 cm	Jumbo .866"		13 mm

~ Made in U.S.A. ~

www.airtools.com

Email: tptinfo@airtools.com

TEXAS
1-800-231-9740
254-587-2533 (Int'l calls)

NEVADA
1-800-858-1222

VIRGINIA
1-800-626-1091

Rivet Buster Steel



Chisel for cutting loose rivets or breaking concrete.

Length	.766" STANDARD		.866" JUMBO	
	For Steel		For Steel	For Concrete Use
9"	1506		2005	2005C
12"	1506-12		2005-12	2005-12C
18"	1506-18		2005-18	2005-18C
24"	1506-24		2005-24	2005-24C

**Must use a split lower sleeve with 24" or longer standard or jumbo chisels*



Chisel for busting heads off tight rivets.

9"	1507		2006	
12"	1507-12		2006-12	
18"	1507-18		2006-18	
24"	1507-24		2006-24	

**Must use a split lower sleeve with 24" or longer standard or jumbo chisels*



Ripper Chisel is used to cut out damaged sections of steel sheets in tank cars, oil storage tanks, and water tanks.


9"	1511		2010	
----	------	--	------	--



Moil Point is used for concrete demolition or other hard substances.

9"	1512		2011	2011C
12"	1512-12		2011-12	2011-12C
18"	1512-18		2011-18	2011-18C
24"	1512-24		2011-24	2011-24C

**Must use a split lower sleeve with 24" or longer standard or jumbo moil points.*



Backout Punches are used after rivet heads have been cut to back out tight rivets.

		Rivet Size		Rivet Size	
9"	1508	5/8" Rivet	2007	5/8" Rivet	
12"	1508-12		2007-12		
9"	1509	3/4" Rivet	2008	3/4" Rivet	
12"	1509-12		2008-12		
9"	1510	7/8" Rivet	2009	7/8" Rivet	
12"	1510-12		2009-12		
9"	1515	3/8" Rivet			
12"	1515-12				
9"	1516	1/2" Rivet	2019	1/2" Rivet	
12"	1516-12		2019-12		
9"	1517	1" Rivet	2020	1" Rivet	
12"	1517		2020-12		
18"			2020-18		
9"			2021	1-1/8" Rivet	
12"			2021-12		

NOTE:

****Texas Pneumatic uses a different alloy for chisels and points that will be used for concrete demolition.**