

ROOF CLEAR

Clear Protection for Roof Tiles



Characteristics & Technical Data

% Solids by Weight (+/- 3%):	25%
Gardner Gloss @ 60	85
QUV (ASTM D G-53):	2000 hours <i>with no gloss loss</i>
WT./Gal	8.5 lbs.
Coverage:	200-300 SqFt/Gal @ 2mil DFT
Clean Up:	Water
VOCs:	240 G/L

1. Manufacturer

SurfaceLogix – a Reliance Supply Company

1880 NW 18th Street
Pompano Beach, FL 33069

Phone: 954.971.9111

Fax: 954.971.6623

Email: support@surfacelogix.net

www.surfacelogix.net

2. Product Description

Roof Clear will protect roof tiles and shingles from ultraviolet light fading, mildew, algae and will display a beautiful sheen.

Roof Clear will keep your roof looking clean and new. This unique 100% acrylic coating will repel water, provide alkali resistance and contains the strongest blend of mildewcide and algacide available.

Use for cement roof tiles. Not recommended for clay tiles.

3. Applications

- Keeps roof looking clean and new
- Specifically formulated to protect concrete roof tiles
- Also protects asphalt shingles and concrete block

4. Properties & Special Features

- Repels water
- Natural look with sheen
- Provides alkali resistance
- Helps protect against sun and UV fading
- Contains strongest blend of mildewcides and algacides to inhibit mildew and algae growth

5. Directions

Before you begin: Surfaces must be clean, dry, and free of any contaminants before sealing. Roof Clear's performance is directly related to how thoroughly the surfaced is prepared. All grease, oil and potential contaminants must be removed. Do not apply when the temperature of the air or the surface to be coated is below 50°F.

Read label instructions carefully. Do not apply when the temperature of the air or the surface to be coated is below 50°F. Testing on your surface is always recommended to insure desired results.

Instructions: Stir product. May be sprayed, rolled, or brushed to a clean dry surface. Two coats thinly applied give the best results. May be sprayed, rolled, or brushed to a clean dry surface. Two coats thinly applied give the best results.

Applications

Roller: Surfaces can be applied with a 3/8" to 3/4" nap roller cover.

Sprayer: Pump sprayer or airless sprayer are recommended.

Continued —>

Clears: **Roof Clear**, 137 – 1g, 137 – 5g

Technical Data Sheet

ROOF CLEAR

Clear Protection for Roof Tiles



6. Directions (cont.)

On bare surface: One and sometimes two thin coats (2 dry mils) provide the best results on uncoated tiles.
Over previously sealed: Scrape and sand all loose material prior to application

Cleaning Tools – Use clean water

7. Packaging

Size	Package	Per Case	Units / Pallet
1 gallon	Pail	4	148
5 gallon	Pail	N/A	36

9 pounds per 1 gallon pail, 45 pounds per 5 gallon pail

8. Coverage

1 gal. covers 200 to 300 square feet per coat. Coverage will depend on surface porosity and method of application.

9. Curing Information

Dry to touch: 1 hour
 Recoat: 3 to 4 hours
 Full cure: 48 to 72 hours

10. Storage & Shelf Life

Product must be kept in its original, unopened and tightly sealed container, and stored in a dry and well ventilated place with controlled temperature (50°F to 90°F). Keep sheltered from weather and direct sunlight. In proper storage conditions, the product's shelf life is 12 months following production (see date on packaging). Store product in original container and close lid tightly after each use.

11. Maintenance

Cobble Clean is recommended for routine cleaning. Follow Cobble Clean instructions for dilution ratios.

12. Shipping

Land and sea: NOT REGULATED
 Packing Group: III
 Flash Point: NA

13. Clean Up

Tools may be cleaned with warm water. Once product begins to dry it may be necessary to use SurfaceLogix Reducer or xylene.

14. Health Hazard Information

Eye Contact: **Wear Eye Protection.** May irritate eyes. If in eyes, flush with water for at least 15 minutes.
Inhalation: Use a NIOSH approved respirator.
Ingestion: If swallowed, DO NOT induce vomiting. Seek medical attention.
Skin: Avoid prolonged contact with skin.

Use with adequate ventilation.

Coated surfaces may become slippery. SurfaceLogix non-skid additive should be incorporated in this situation. However, it is the sole responsibility of the applicator to determine whether a non-skid additive is appropriate for the job.

15. Technical Support

For friendly, knowledgeable and courteous technical support please call 954.971.9111.

You may also reach us by sending a query from our website at www.surfacelogix.net.

16. Disclaimer

All SurfaceLogix products are manufactured with the finest raw materials. It is the applicator's responsibility to determine the appropriate use of the product.

All recommendations and suggestions are made without guarantee, since conditions of use are beyond our control.