

• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®

RUST REFORMER®



**INSTANTLY
CONVERTS
RUST**
to a protected,
paintable
surface!

**STOPS
RUST®**

NET WT. 8 OZ. 236mL

Rust-Oleum® Stops Rust® Rust Reformer® instantly bonds with rust and transforms it to a non-rusting, flat-black paintable surface as well as preventing future rust. It saves you the effort of sanding rust all the way down to bare metal. Rust Reformer is odorless, water soluble, completely safe and easy to apply.

Preparation: Remove flaking paint and rust with sandpaper. Clean with soap and water, rinse and let dry. **WARNING!** If you scrape, sand or remove old paint, you may release lead dust.

LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Application: Shake well. Apply Rust Reformer to rusted surfaces directly from the bottle or pour needed amount into a bowl, then apply using a brush. After 15 minutes, Rust Reformer will dry to a black surface.

Painting: For oil based paint, wait 4 hours after Rust Reformer has dried before painting. For lacquer or aerosol paint, wait 3 days. If no top coat is desired, a second application of Rust Reformer is recommended.

Clean up: Spills should be cleaned up immediately with water.

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact our Customer Service Department for a full refund of the purchase price. Refer to product number and batch code on bottom of can.



An **RPM** Company

rustoleum.com

RUST-OLEUM®
CORPORATION

11 Hawthorn Pkwy., Vernon Hills, IL 60061

1-800-481-4785

• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM® RUST REFORMER®



**INSTANTLY
CONVERTS
RUST**
to a protected,
paintable
surface!

**STOPS
RUST®**

DANGER! EXTREMELY FLAMMABLE.
VAPOR HARMFUL. VAPORS MAY CAUSE
FLASH FIRE. CONTENTS UNDER PRESSURE.
See other cautions on back panel.

¡PELIGRO! EXTREMADAMENTE INFLAMABLES.
VAPORS NOCIIVOS. PUEDEN CAUSAR UN
INCENDIO REPENTINO. NO SOMETER A PRESI N.
Observar otras precauciones al dorso.

NET WT. 10.25 OZ. 291g

Rust-Oleum® Stops Rust® Rust Reformer® instantly transforms rusted metal to a non-rusting surface as well as preventing future rust. This unique formula bonds with rust to convert it to an easily paintable surface, saving you the effort of sanding rust all the way down to bare metal. For best rust protection, use a Rust-Oleum® finish for topcoat application. Ideal uses include railings, patio furniture and mailboxes.

Painting Conditions: Use outdoors or in a well-ventilated area such as an open garage. Use when temperature is above 50°F (10°C) and humidity is below 85% to ensure proper drying. Do not apply to surfaces that exceed 200°F (93°C) or galvanized metal. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

Preparation: Remove loose, flaking rust with sandpaper. Clean with soap and water, rinse and let dry. **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Painting: Shake can vigorously for one minute after mixing ball begins to rattle. Shake often during use. Hold can upright 10-16" from the surface and spray in a steady back and forth motion, slightly overlapping each stroke. The applied surface will turn black. Maintain same distance from the surface while spraying. Rust-Oleum® Stops Rust® Rust Reformer® can be applied to rusted and adjacent surfaces.

Recoat Times: One coat is sufficient for optimal performance.

Dry Time: Allow to dry for 24 hours.

Top Coat Application: If desired, apply a top coat color of your choice after 24 hours. For maximum top coat adhesion and rust prevention, use Rust-Oleum® Stops Rust® paint.

Clean-up: When finished spraying, clear spray valve by turning can upside down and pushing spray button for 5 seconds. Clean up wet or dry paint with Xylol. Mineral spirits can also be used to remove wet paint. Throw away empty can in trash pickup. Do not burn or place in home trash compactor.

Clogging: If valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not stick a pin or other objects into the stem.



CONTAINS TOLUENE, ACETONE AND XYLENE. VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Do not breathe vapors, spray mist, sanding dust or overspray. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA approved) or leave the area. Avoid contact with eyes, skin and clothing. **Vapors may ignite explosively.** Keep away from heat, sparks and flame. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Do not smoke. **Use only with adequate ventilation.** Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Do not expose to heat or store at temperatures above 120°F. Exposure to heat or prolonged exposure to sun may cause bursting. Do not puncture or incinerate (burn) container. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. **WARNING:** This product contains a chemical known to the state of California to cause cancer and birth defects or other reproductive harm. **KEEP OUT OF REACH OF CHILDREN. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL. DO NOT STORE ABOVE 120°F (48°C). Unleaded—Safe for use on children's toys, furniture, etc. For emergency, call your physician, local poison control center or local emergency room. For product health information, call: (847) 367-0244.**

ADVERTENCIA. CONTIENE TOLUENO, ACETONA Y XILENO. LAS EMANACIONES SON DAÑINAS. PUEDEN AFECTAR EL CEREBRO O EL SISTEMA NERVIOSO CAUSANDO MAREOS, JAQUECAS O NAUSEA. IRRITA LOS OJOS, LA PIEL, LA NARIZ Y LA GARGANTA. AVISO: En algunos estudios se ha observado que la sobreexposición prolongada a los solventes causa daño permanente al cerebro y al sistema nervioso. No aspire las emanaciones, la neblina del rocío o el polvo del lijado, ni el rocío, abra las ventanas y puertas o emplee cualquier otro medio para asegurar la circulación de aire fresco durante la aplicación y el secado. Si experimenta lacrimación en los ojos, jaquecas o mareos, aumente la circulación de aire fresco o póngase protección respiratoria (con certificación NIOSH/MSHA) o abandone el área. Evite contacto con los ojos, la piel y la ropa. **Las emanaciones pueden inflamarse explosivamente.** Manténgalo alejado de fuentes caloríficas, chispas y flamas. Durante la aplicación del producto, apague las flamas y pilotos, apague los hornos, calentadores, motores eléctricos y todas las otras fuentes de ignición hasta que todas las emanaciones hayan

desaparecido. No fume. **Aplique el producto solamente con ventilación adecuada.** Evite la acumulación de emanaciones abriendo todas las ventanas y puertas para lograr ventilación en todas las direcciones. No exponga el recipiente al calor ni lo almacene a temperaturas superiores a 120°F (48°C). La exposición al calor, o la exposición prolongada al sol puede causar que estalle. No perforo ni incinere (o quemé) el recipiente. **PRIMEROS AUXILIOS:** Si sufre dificultad para respirar, abandone el área y respire aire fresco. Si la dificultad para respirar persiste, busque asistencia médica inmediatamente. En caso de contacto con los ojos, enjuáguelos de inmediato con suficiente agua durante un mínimo de 15 minutos y busque atención médica. **ADVERTENCIA:** Este producto contiene químicos que son conocidos en el estado de California porque causan cáncer y defectos de nacimiento u otros daños al sistema reproductivo. **MANTÉNGALO FUERA DEL ALCANCE DE LOS NIÑOS. EL USO INAPROPIADO INTENCIONAL CONCENTRANDO E INHALANDO EL CONTENIDO PUEDE SER DAÑINO O MORTAL. NO SE DEBE ALMACENAR A TEMPERATURAS SUPERIORES A 120°F (48°C). No contiene plomo—Puede utilizarse para los juguetes de los niños, muebles, etc. Para conseguir información emergencia sobre el producto y los posibles efectos en la salud, llame al: (847) 367-0244. PROHIBIDA SU VENTA A MENORES DE EDAD; PRODUCTO ORIGINARIO DE E.U.A.**

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact our Customer Service Department for a full refund of the purchase price. Refer to product number and batch code on bottom of can.

Contains no GFC's

RUST-OLEUM®
CORPORATION

An **rpm** Company
rustoleum.com

11 Hawthorn Pkway, Vernon Hills, IL 60061
1-800-481-4785 paintideas.com



©2004 Rust-Oleum Corporation Made in USA 215412 0804