



**NEWLOOK**

# NewLook International, Inc. Gription™

## Technical Information Sheet

NewLook International, Inc. Gription™ is a micronized polymer used as an additive to sealers, paints and other coatings to improve slip resistance. This fine grit can also be used as an additive to coatings for fine texturing and gloss reduction.

### FEATURES AND BENEFITS

- Low density
- Low oil absorption
- High solvent resistance
- Easily stirs in to most oil and water based coatings
- Adds traction to slippery inclines or areas

### RECOMMENDED USAGE

- Oil based paints
- Oil based sealers or coatings
- Water based paints
- Water based sealers or coatings

### PRODUCT DATA

- Appearance: White Granular.
- One 4 oz bottle mixes into 1 gallon of a coating
- One 1 lb. bottle mixes into 5 gallons of a coating

### DISPOSAL

Dispose of waste in accordance with applicable environmental and governmental regulations.

### DIRECTIONS FOR USE

1. Add 4 oz of NewLook Gription to one gallon of stain or sealer to provide slip resistance to your surface.
2. Apply your stain or sealer following package label instructions.

### STORAGE

- Store product indoors, away from heat, moisture, and direct sunlight.
- Keep containers tightly sealed.

### CAUTION

KEEP AWAY FROM CHILDREN AND ANIMALS. Before using or handling, read the MSDS and Product Instructions. DO NOT CONSUME. Avoid contact with eyes and skin. Wear rubber gloves, aprons and safety eye goggles. Use good hygiene when handling this product. It is recommended that you wash and bathe after each use. Avoid inhalation and only use product in a well ventilated area.

### PACKAGING AND COVERAGE

Kit Type	Number of Containers	Size
Skid Resistant Additive	4 oz	Mixes into 1 gallon of coating
	1 lb	Mixes into 5 gallons of coating

### WARRANTY

NewLook International, Inc. Gription™ ("Product") is not intended for public use and are intended for use by licensed contractors and installers, experienced and trained in the use of these products. Product is warranted to be of uniform quality within manufacturing tolerances. The manufacturer has no control over the use of Product, therefore no other oral or written representation or statement of any kind, express or implied, now or hereafter made is authorized or warranted by NewLook International, Inc. or its affiliates, and NewLook International, Inc. and its affiliates hereby disclaims all such warranties, including those of merchantability or fitness for a particular purpose. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven to be defective. NewLook International, Inc. shall not be liable for special, incidental, or consequential damages, including delays or lost profits. Communication of this warranty and its limitations to end users is not the responsibility of NewLook International, Inc. but should be communicated by those in direct contact with the end user. Any claim regarding product defect must be received in writing within one year from the date of manufacture. No claim will be considered without such written notice or after the specified time interval. The end user shall be responsible for determining Product's suitability and assumes all risks and liability.