



Sometimes it's about more than just light. With our multiple socket tower, available with or without light, another gap in our range is filled. Design your garden even more flexibly, in proven DEKO-LIGHT quality of course and at a price that won't break the bank.

Special features

- Safe power distribution outdoors
- Total load max. 3,680 W
- Outlets and lights can be switched on separately
- Connection box with IP67 and accessories including in scope of delivery
- Feed-through wiring possible

Housing Material	Die-cast aluminium	Life Time L70 / B50	25000 h
Housing Color	Gray	Switching Cycles	100000
Material of Lens	Plastic	Power Consumption	5 kWh/1000h
Colour of Lens	White	Energy Efficiency Class	F
Protection Class	Protection class I/protective grounding		
Rated Input	4.8 W		
Rated Input Voltage min./max. Frequency	220-240 V/AC 50 / 60 Hz		
Rated Current	16 A		
Power Supply Unit incl.	Yes		
Connection Cable Primary	Yes		
Primary Connection	Connection box IP67		
Control	No		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	150 lm		
Rated Angle of Reflection	360 Degree		
Distribution Characteristic 120°	NDLS		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Side		
Height	478 mm		
Diameter	100 mm		
Working Temperature	-20 to 50 °C		
Storage Temperature	-10 to 60 °C		
IP Protection Class	IP 44		