

Safety Data Sheet

Product: Ameripolish® Strip and Clean

SDS No: 85-110A

SECTION 1 GENERAL INFORMATION



Ameripolish®
120 Commercial AVE
Lowell, AR 72745, USA

Telephone: 479-725-0033
In case of emergency call chemtrec: 1-800-424-9300
Outside of U.S.A.: 001-703-527-3887
Date: 4/5/2005

SECTION 2 HAZARD(S) IDENTIFICATION

GHS - Classification

Eye Damage/Irritation (Category 1)
Skin Corrosion/Irritation (Category 1) (Category 1B)
Acute Toxicity - Oral (Category 4)
Specific Target Organ Toxicity (Single Exposure) (Category 3)

Signal Word:

Danger



Hazard Statement(s)

H302 Harmful if swallowed
H314 Causes severe skin burns and eye damage
H335 May cause respiratory irritation

Precautionary Statement(s)

P261 Avoid breathing dust/ mist/ vapours.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for 15 minutes or more. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER.
P280 Wear protective gloves/eye protection/protective clothing.
P501 Dispose of contents in container in accordance with local/state/federal/international regulations.

SECTION 3 COMPOSITION/ INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS#	PERCENTAGE
PROPRIETARY COMPONENT	TRADE SECRET	<20

SPECIFIC CHEMICAL NAME(S) AND CAS NUMBER(S) MAY BE A TRADE SECRET AS ALLOWED BY 29 CFR 1910.1200

SECTION 4 FIRST AID MEASURES

EYES: FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES, OCCASIONALLY LIFTING EYELIDS. GET MEDICAL ATTENTION.
SKIN: FLUSH SKIN WITH WATER FOR AT LEAST 15 MINUTES WHILE REMOVING CONTAMINATED CLOTHES. LAUNDRER BEFORE REUSE.
INGESTION: DO NOT INDUCE VOMITING. GIVE LARGE QUANTITIES OF WATER TO DILUTE. KEEP PATIENT WARM AND QUIET AND GET IMMEDIATE MEDICAL ATTENTION.
INHALATION: IF AFFECTED, REMOVE INDIVIDUAL TO FRESH AIR.

SECTION 5 FIRE FIGHTING MEASURES

FLASH POINT: N.A.
EXTINGUISHING METHOD: USE WATER, WATER SPRAY, OR WATER FOG.
SPECIAL FIRE FIGHTING PROCEDURES: USE SELF CONTAINED BREATHING APPARATUS.
UNUSUAL FIRE FIGHTING PROCEDURES: NONE KNOWN.

SECTION 6 ACCIDENTIAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Ensure adequate ventilation. Keep people away from and upwind of spill/leak.
ENVIRONMENTAL PRECAUTIONS: Avoid subsoil penetration. Do not flush into surface water or sanitary sewer system. Advise water authority if spillage

ND = NOT DETERMINED NA = NOT APPLICABLE

Safety Data Sheet

Product: Ameripolish® Strip and Clean

SDS No: 85-110A

has entered water course or drainage system.

METHODS FOR CLEAN UP: Use mechanical handling equipment. Soak up with inert absorbent material(e.g. sand, silica gel, acid binder, universal binder, sawdust)

SPILL: VENTILATE AREA, PERSONS PERFORMING CLEAN-UP SHOULD WEAR ADEQUATE PROTECTION EQUIPMENT. CONTAIN MATERIAL BY DIKING THE AREA AROUND THE SPILL. IF THE PRODUCT IS IN A SOLID FORM, SHOVEL DIRECTLY INTO RECOVERY DRUMS. IF THE PRODUCT IS A LIQUID, IT SHOULD BE PICKED UP USING A SUITABLE ABSORBANT MATERIAL, THEN SHOVELED TO RECOVERY DRUMS. IF THE MATERIAL IS RELEASED INTO THE ENVIRONMENT, THE USER SHOULD DETERMINE WHETHER THE SPILL SHOULD BE REPORTED TO THE APPROPRIATE LOCAL, STATE AND FEDERAL AUTHORITIES.

SECTION 7 HANDLING AND STORAGE

HANDLING AND STORAGE: MATERIAL SHOULD BE STORED IN ITS OWN CONTAINER AND SHOULD ALWAYS BE KEPT COVERED WHEN NOT IN USE.

SECTION 8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

ROUTES OF EXPOSURE: EYES SKIN INGESTION INHALATION

SYMPTOMS OR ACUTE HEALTH HAZARDS

EYES: CAUSES EYE IRRITATION.
SKIN: PROLONGED CONTACT MAY CAUSE BURNS.
INGESTION: WILL CAUSE NAUSEA, VOMITING, IRRITATION.
INHALATION MAY CAUSE IRRITATION OF NOSE, THROAT AND UPPER RESPIRATORY TRACT.

RESPIRATORY PROTECTION: IF NEEDED, USE A NIOSH APPROVED RESPIRATOR.
VENTILATION USE SUFFICIENT MECHANICAL(GENERAL)OR LOCAL EXHAUST.

PROTECTIVE EQUIPMENT: GLOVES FACESHIELD APRON GOGGLES IMPERVIOUS COVERALLS

WORK/ HYGIENIC PRACTICES: AS WITH ALL INDUSTRIAL CHEMICALS, CARE SHOULD BE TAKEN TO AVOID CONTACT WITH EYES, SKIN, AND CLOTHING. HANDS AND UNPROTECTED SKIN SHOULD BE THOROUGHLY WASHED AND CONTAMINATED CLOTHING SHOULD BE CHANGED PRIOR TO ANY DIRECT PERSONAL CONTACT. ALL EXPOSED CLOTHING SHOULD BE LAUNDERED PER NORMAL CARE INSTRUCTIONS BEFORE REUSE

EXPOSURE LIMITS

SODIUM METASILICATE

LIMITS

N.D.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

PH:	11-13	AS IS	Evaporation Rate:	NO DATA
SOLUBILITY:	SOLUBLE		Vapor Pressure:	NO DATA
SPECIFIC GRAVITY:	1.080-1.130		Vapor Density:	NO DATA
APPEARANCE:	AMBER LIQUID		Auto Ignition Temperature:	NO DATA
Bod:	NO DATA		LEL:	NO DATA
Cod:	NO DATA		UEL:	NO DATA
Odor:	NO DATA		VOC:	N/D
OdorThreshold:	NO DATA		FlashPoint:	N.A.
MeltingPoint:	NO DATA			
BoilingPoint:	NO DATA			

SECTION 10 STABILITY AND REACTIVITY

STABILITY: STABLE
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR
DECOMPOSITION PRODUCTS: NOT ESTABLISHED
CONDITIONS AND MATERIALS TO AVOID: NONE KNOWN

SECTION 11 TOXICOLOGICAL INFORMATION

ND = NOT DETERMINED NA = NOT APPLICABLE

Safety Data Sheet

Product: Ameripolish® Strip and Clean

SDS No: 85-110A

ACUTE TOXICITY: LD50(ORAL) RAT 847MG/KG
Chronic Toxicity: NO DATA
Carcinogenicity: NO DATA
Target Organ Effects: CAN CAUSE RESPIRATORY IRRITATION

This product has not yet been tested. The information is derived from the properties of the individual components.

SECTION 12 ECOLOGICAL INFORMATION

Ecotoxicity: NO DATA
Persistence Degradability: NO DATA
Bioaccumulation: NO DATA
Mobility: NO DATA

This product has not yet been tested. The information is derived from the properties of the individual components.

SECTION 13 DISPOSAL CONSIDERATIONS

Disposal of this product should be made in accordance with federal state and local regulations.

SECTION 14 TRANSPORT INFORMATION

TRANSPORTATION: UN3267 CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S
(SODIUM METASILICATE)
8 PG II

SECTION 15 REGULATORY DATA

TITLE III-SARA: THE FOLLOWING DATA IS BEING SUPPLIED IN COMPLIANCE WITH TITLE III SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT (SARA) PART 313 AND 40 CFR 372
THIS PRODUCT DOES NOT CONTAIN ANY CHEMICALS FOUND ON THE SARA LIST IN 40 CFR 372.

CALIFORNIA PROPOSITION 65 CONTAINS NO MATERIALS KNOWN TO BE ON THE CALIFORNIA PROPOSITION 65 LIST.

SECTION 16 OTHER INFORMATION

Large Spill: Isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids.
Fire: If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

DISCLAIMER

THE INFORMATION GIVEN HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE WHETHER ORIGINATING WITH THIS COMPANY OR NOT. THE INFORMATION IS OFFERED SOLELY FOR YOUR CONSIDERATION. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED THAT THE INFORMATION IS CURRENT AND SUITABLE FOR THEIR NEEDS.

End of SDS