

ARDEX FEATHER FINISH®

Self-Drying, Cement-Based Finish Underlayment

ARDEX FEATHER FINISH mixes to a creamy, smooth finish underlayment that eliminates flooring installation problems associated with disbonding, crumbling, mold, mildew and staining. ARDEX FEATHER FINISH may be used as an embossing filler when mixed with ARDEX P 82™ Ultra Prime.

Install over: concrete, masonry, wood, terrazzo, and ceramic and quarry tile - as well as properly prepared residues of cutback and other non-water-soluble adhesives on concrete - all without the need for priming or the use of a latex additive

Key Features

- Blend of hydraulic and other cements
- Self-drying matrix
- Mixes with water only
- Trowelable
- Mold and mildew resistant
- Interior use

Installation

- **General priming recommendations:**
 - Porous surfaces: No priming required
 - Most non-porous surfaces (epoxy coating systems, metal and concrete treated with silicate compounds) must be primed with ARDEX P 82™ Ultra Prime
 - Gypsum underlayment - Use ARDEX P 51™ Primer
- **Packaging:** 10 lb. (4.5 kg)
- **Coverage:** Up to 300 sq. ft. per bag (27.9 m²)
- **Thickness:**
 - True Featheredge
 - 1/2 in. (13 mm) over large areas
 - Any depth in small areas
- **Pot life:** 20 minutes (may be retempered)
- **Install floor coverings:** 15 minutes

Performance

- **VOC:** 0



SUBSTRATE
PREPARATION



AMERICAS

888-512-7339

+1-724-203-5000

www.ardexamericas.com

AF127 03/15