System Overview



ROCKHARD USA PREMIUM EPOXY KIT

DESCRIPTION

Xtreme's Rockhard USA Epoxy is a self-leveling concrete floor coating system that produces seamless and gleaming finishes while obtaining absolute resilience and sustainability. Our new and improved Rockhard formula is designed for high-performance applications, including concrete floors, commercial kitchens, industrial settings, garage flooring, counter tops, and other high-traffic environments.

FEATURES & BENEFITS

- 100% solids, self-leveling, and VOC compliant.
 Non-toxic, environmentally friendly, and resistant to harsh chemicals.
- Several layers can be applied over itself.
- It exhibits excellent bonding properties.
- It creates a dense surface that resists bacteria and moisture.
- You can use it indoors safely without producing harmful odors.

PRODUCT CODE

ROCKHARDUSAX-KIT

SPECS

Format: 3 Gallon Kit 2 Gallons Part A: Part B: 1 Gallon

Mix Ratio: Resin (A) / Hardener (B) = 3/1

Curing Time	41°F	68°F	86°F
Set-to-touch	10 Hours	5 Hours	3 Hours
Dry-through	32 Hours	16 Hours	10 Hours
Over-coat (Max)	48 Hours	36 Hours	18 Hours
Full Cure	9 Days	4 Days	3 Days
Pot Life	60 Minutes	40 Minutes	10 Minutes



Solids: 100% Color: Clear Finish: Gloss Shelf Life: 12 months



Coverage Rates (Sy	stem) Coverage Rates (Gal/Kit)
Flake Floor Base Coat	1 Coat @ 150 SF/Gal - 450 SF/Kit
Solid Color Floor	2 Coats @ 100 SF/Gal - 300 SF/Kit
Metallic Floor	1 Coat (Base) @ 100 SF/Gal - 300 SF/Kit 1 Coat (Decorative) @ 30-40 SF/ Gal - 90-120 SF/Kit
Clear Coat	1 Coat @ 100 SF/Gal - 300-600 SF/ Kit

AFOREMENTIONED POT LIFE AND FOLLOW-UP COATING TIME HAVE BEEN MEASURED UNDER LABORATORY CONDITIONS AND MAY VARY DEPENDING ON CONSTRUCTION SITE.

PRODUCTS FREQUENTLY BOUGHT TOGETHER

DESCRIPTION	USAGE	PRODUCT CODE
24" Notch Squeegee	Reusage	WB-R7153
24" Magic Squeegee Trowel	Reusage	XPS-24TR0WEL
18" Big Ben brush: Roller Frame	Reusage	WB-BR045
18" Painters Solution: Roller Cover	Consumable	WB-R575-18
Epoxy Coatings Spiked Shoes	Reusage	SH0ES-EP0XYPR0
Color Additives: Powder Pigments (Metallic)	Consumable	XPS+Color
Color Additives: Liquid Pigments (Solid or Metallic)	Consumable	4CB+Color or CM+Color
Color Additives: Flakes (Mica Chips)	Consumable	XPS-MICA+Color
Color Additives: Flakes (Vinyl Chips)	Consumable	XPS-SIGNATURE+Color
Color Additives: Glitter (Fine or chunky)	Consumable	GMWMC+Color



